

XStream®-PKG RF Modems

100 mW/900 MHz or 50 mW/2.4 GHz Stand-Alone Radio Modems

900 MHz and 2.4 GHz stand-alone RF modems provide outstanding range (up to 20 miles) in a low-cost wireless solution.




Overview

Digi's XStream-PKG RF modems can be configured in minutes to provide low-cost serial cable replacement between all types of electronic devices. Available in 900 MHz and 2.4 GHz models, XStream-PKG modems provide transmission ranges of up to 20 miles in a low-cost wireless solution. The modems are coupled with a DIP-switchable RS-232/422/485 interface board and regularly outperform more expensive RF modems.

Innovations stamped in their design enable XStream-PKG modems to yield two- to eight-times the range of competing modems. This allows OEMs and integrators to cover more ground with fewer devices. Additionally, XStream-PKG modems are easy to use, thereby reducing the complexity of data system development.

Available in a variety of data interface options, including RS-232/422/485 serial, USB and telephone, XStream-PKG modems can wirelessly connect a variety of devices across many applications including remote monitoring, building automation/security, industrial automation/SCADA, fleet management/asset tracking and sensor data capture in embedded systems.

Application Highlight



Features/Benefits

- Indoor/Urban range up to 1500 feet
- Outdoor line-of-sight range up to 20 miles (with high gain antenna)
- 7 frequency hopping channels, each with 65K available addresses
- Outstanding receiver sensitivity (-110 dB @9600 bps)
- Low power consumption for power-sensitive applications
 - Pin, serial port and cyclic sleep modes available
- Performs retries and acknowledgments for reliable packet delivery
- Easy out-of-the-box operation — no configuration necessary
- Durable industrial grade enclosure



Features/Specifications

PERFORMANCE

- Indoor/Urban range (w/ 2.1 dB dipole antenna):
 - Up to 1500 feet (450 m) @ 900 MHz
 - Up to 600 feet (180 m) @ 2.4 GHz
- Outdoor RF line-of-sight range (w/ 2.1 dB dipole antenna):
 - Up to 7 mi (11 km) @ 900 MHz
 - Up to 3 mi (5 km) @ 2.4 GHz
- Outdoor RF line-of-sight range (w/ high gain antenna):
 - Up to 20 mi (32 km) @ 900 MHz
 - Up to 10 mi (16 km) @ 2.4 GHz
- Transmit power output:
 - 100 mW (20 dBm) @ 900 MHz
 - 50 mW (17 dBm) @ 2.4 GHz
- Receiver sensitivity:
 - 900MHz: -110 dBm (@9,600 bps throughput data rate), -107 dBm (@19,200 bps)
 - 2.4 GHz: -105 dBm (@9,600 bps throughput data rate), -102 dBm (@19,200 bps)
- Interface data rate (software selectable): 10 - 57600 bps (including non-standard baud rates)
- Throughput data rate: 9,600 or 19,200 bps
- RF data rate: 10,000 bps (@9,600 bps throughput data rate) or 20,000 bps (@19,200 bps)

DIMENSIONS

XStream-PKG-R, XStream-PKG-U,

- Length: 2.75 in (6.99 cm)
- Width: 5.50 in (13.97 cm)
- Depth: 1.12 in (2.86 cm)
- Weight: 7.10 oz (200.00 g)

XStream-PKG-T

- Length: 2.75 in (6.99 cm)
- Width: 6.50 in (16.51 cm)
- Depth: 1.50 in (3.80 cm)
- Weight: 8.10 oz (228.00 g)

CONNECTION OPTIONS

- RS-232/485 DB-9 (XStream-PKG-R)
- USB (XStream-PKG-U)
- Telephone RJ-11 (XStream-PKG-T)

POWER REQUIREMENTS

XStream-PKG-R

- Power supply voltage: 7 - 18V
- Receive current:
 - 70 mA @ 900 MHz
 - 90 mA @ 2.4 GHz
- Transmit current:
 - 170 mA @ 900 MHz
 - 180 mA @ 2.4 GHz
- Power Down Current: < 1 mA

XStream-PKG-U

- Power supply voltage: 5 - 12V
- Receive current:
 - 90 mA @ 900 MHz
 - 115 mA @ 2.4 GHz
- Transmit current:
 - 185 mA @ 900 MHz
 - 200 mA @ 2.4 GHz
- Power Down Current: 50 mA

XStream-PKG-T

- Power supply voltage: 7 - 28V
- Receive current:
 - 140 mA @ 900 MHz
 - 160 mA @ 2.4 GHz
- Transmit current:
 - 220 mA @ 900 MHz
 - 230 mA @ 2.4 GHz
- Power down current: n/a


NETWORKING AND SECURITY

- Frequency: ISM 902 - 928 MHz or 2.4000 - 2.4835 GHz
- Spread Spectrum: FHSS (Frequency Hopping Spread Spectrum)
- Modulation: FSK (Frequency Shift Keying)
- Supported network topologies: Peer-to-peer (no master/slave dependencies), point-to-point, point-to-multipoint and multidrop
- Channel capacity (software selectable): 7 hopping sequences
- Network filtration layers: VID, Hopping Channel & Destination Address


ANTENNA

- Connector options: RPSMA (Reverse Polarity SMA)
- Impedance: 50 ohms unbalanced


XStream-PKG-R - Front



XStream-PKG-R - Back



XStream-PKG - Side



ENVIRONMENTAL

All models

- Operating temperature: 0° C to 70° C (commercial)
- Operating temperature: -40° C to 85° C (industrial)

CERTIFICATIONS

- FCC ID (U.S. Certification Part 15.247)
 - OUR9XSTREAM (900 MHz),
 - OUR-24XSTREAM (2.4 GHz)
- IC ID (Canada)
 - 4214A-9XSTREAM (900 MHz),
 - 4214A 12008 (2.4 GHz)
- Europe
 - ETSI, CE (2.4 GHz only)

Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

**Digi International
Worldwide HQ**

877-912-3444
952-912-3444

**Digi International
France**

+33-1-55-61-98-98
www.digi.fr

**Digi International
Japan**

+81-3-5428-0261
www.digi-intl.co.jp

**Digi International
India**

+91-80-4287-9887

**Digi International
Singapore**

+65-6213-5380

**Digi International
China**

+86-21-5150-6898
www.digi.cn



91001400
81/911

BUY ONLINE • www.digi.com

© 2005-2011 Digi International Inc. All rights reserved. Digi, Digi International, the Digi logo, the Wireless M2M logo and XStream are trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective owners.

info@digi.com



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Digi International:

[X24-009PKC-RA](#) [X24-009PKC-UA](#) [X24-019PKC-RA](#) [X24-019PKC-UA](#) [X24-009PKT-RA](#) [X24-009PKI-RA](#) [X24-019PKT-R](#) [X24-019PKI-RA](#) [X24-009PKT-R](#) [X24-009PKI-TA](#) [X09-019PKI-TA](#) [X24-009PKI-R](#) [X24-019PKI-R](#) [X24-009PKC-R](#) [X24-019PKC-R](#) [X24-009PKC-U](#) [X24-019PKC-U](#) [X24-009PKC-EA](#) [X24-019PKC-EA](#) [X24-009PKC-E](#) [X24-019PKC-E](#) [X24-019PKT-RA](#) [XH9-009PKC-RA](#) [XH9-009PKC-E](#) [XH9-019PKC-EA](#) [XH9-019PKC-U](#) [XH9-019PKC-RA](#) [XH9-009PKC-EA-W](#) [XH9-019PKC-R](#) [XH9-009PKC-R](#) [XH9-019PKC-E](#) [XH9-009PKC-U](#) [XH9-009PKC-UA](#)