

Part Number	V_{RWM} (V)	$I_{FAV}@T_C$ (A)	$V_{FM}@I(AV)$ (V)	I_{FSM} @60Hz (A)	Max t_{rr} (ns)	$R_{\theta JC}$ (°C/W)	Notes	Fax on Demand Number	Case Outline Key
-------------	------------------	----------------------	-----------------------	---------------------------	----------------------	---------------------------	-------	----------------------	------------------

SMB

10BF10	100	1	120	0.95	30	35	25	3 6	J2
10BF20	200	1	120	0.95	30	35	25	3 6	
10BF40	400	1	75	1.3	30	50	30	3 6	
10BF60	600	1	75	1.5	30	100	30	3 6	
10BF80	800	1	75	1.7	30	100	30	3 6	

SMC

30BF10	100	3	120	0.95	60	35	12	3 6	J3
30BF20	200	3	120	0.95	60	35	12	3 6	
30BF40	400	3	75	1.4	60	50	15	3 6	
30BF60	600	3	75	1.5	60	100	15	3 6	
30BF80	800	3	75	1.7	60	100	15	3 6	

NOTES:

3 Available on tape-and-reel

6 For Ifsm: Following any rated load condition and with VR

WM reapplied

Illustrations not to scale



SMB



SMC

