




- NOTES:
- 1.DISPLAY TYPE STN or FSTN
 - 2.VIEWING DIRECTION: 6:00 or 12:00
 - 3.POLARIZER MODE: TRANSMISSIVE or TRANSFLECTIVE
 - 4.OPERATING TEMP.: NORMAL or WIDE
 - 5.STORAGE TEMP.: NORMAL or WIDE
 - 6.DRIVE VOLTAGE(VDD): 5.0V
 - 7.DRIVERS: S6B2086X01-TORA
 - 8.LCD OPERATING VOLTAGE:12.0V VEE=-7.0V
 - 9.LCD DRIVE METHOD: DUTY=1/64 BIAS=1/9
 - 10.ALL UNMARKED TOLERANCES:±0.2
 - 11.BACKLIGHT TYPE: LED<4.2V DC,YELLOW-GREEN>
 - 12.BEZEL IS TO BE PAINTED BLACK
 - 13.LIMITING RESISTOR FOR BACKLIGHT VALUE: 2.0ohm,1W
 - 14.TEMPERATURE COMPENSATION CIRCUIT ON PCB

1	D1
2	FLM
3	M
4	CL1
5	CL2
6	NC
7	VDD
8	VSS
9	VEE
10	NC



 TIAN-MA MICROELECTRONICS CO. 22/F., HANGDU Building, Shennan Road, Central, Shenzhen, China			
DRAWN BY:		TITLE: TM24064N series	 SCALE: UNITS: mm
CHECKED BY:		DWG NO: G-3	
APPROVED BY:		DWG NAME: TM24064N G-3	
CONFIRMED BY:		SHEET NO: 01	