




1.25-W MONO FULLY DIFFERENTIAL AUDIO POWER AMPLIFIER



DESCRIPTION

The UTC **PA6203** is a mono fully-differential audio amplifier, capable of delivering 1.25W of continuous average power to an 8-Ω BTL load with less than 1% distortion from a 5V power supply.

The UTC **PA6203** is ideal for PDA/smart phone applications due to features such as -85-dB supply voltage rejection from 90Hz to 5kHz, improved RF rectification immunity and a fast start-up with minimal pop. The device operates from 2.5V to 5.5V, drawing only 1.7mA of quiescent supply current.

FEATURES

- * 1.25W into 8Ω from a 5-V supply at THD=1% (Typ.)
- * 2.5V-5.5V operation
- * Low supply current: 1.7mA typ at 5V
- * Shutdown Control < 10μA
- * Only five external components
 - Improved PSRR (90dB) for direct battery operation
 - Fully differential design reduces RF rectification
 - Improved CMRR eliminates two input coupling capacitors
 - C_(BYPASS) is optional due to fully differential design and high PSRR

APPLICATIONS


- * Designed for wireless or cellular handsets and PDAs

ORDERING INFORMATION

| Ordering Number | | Package | Packing |
|-----------------|---------------|---------|-----------|
| Lead Free | Halogen Free | | |
| PA6203L-SH2-T | PA6203G-SH2-T | HSOP-8 | Tube |
| PA6203L-SH2-R | PA6203G-SH2-R | HSOP-8 | Tape Reel |

| | |
|--|--|
| <p>PA6203L-SH2-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Halogen Free</p> | <p>(1) T: Tube, R: Tape Reel</p> <p>(2) SH2: HSOP-8</p> <p>(3) L: Lead Free, G: Halogen Free</p> |
|--|--|


■ PIN CONFIGURATION



■ PIN DESCRIPTION

| PIN NO. | PIN NAME | DESCRIPTION |
|---------|-----------------|--|
| 1 | SHUTDOWN | Shutdown terminal (active low logic) |
| 2 | BYPASS | Mid-supply voltage, adding a bypass capacitor improves PSRR |
| 3 | IN+ | Positive differential input |
| 4 | IN- | Negative differential input |
| 5 | V _{O+} | Positive BTL output |
| 6 | V _{DD} | Supply voltage terminal |
| 7 | GND | High-current ground |
| 8 | V _{O-} | Negative BTL output |
| | Thermal Pad | Connect to ground. Thermal Pad must be soldered down in all applications to properly secure device on the PCB. |

■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING (Over operating free-air temperature range, unless otherwise noted)

| PARAMETER | SYMBOL | RATINGS | UNIT |
|---|--------------------------------|--------------------|------|
| Supply Voltage | V_{DD} | -0.3~6 | V |
| Input Voltage | INx and SHUTDOWN Pins V_I | -0.3~ $V_{DD}+0.3$ | V |
| Continuous Total Power Dissipation | P_D | Internally Limited | |
| Operating Free-air Temperature | T_A | -40~85 | °C |
| Junction Temperature | T_J | -40~125 | °C |
| Storage Temperature | T_{STG} | -65~150 | °C |
| Lead Temperature From Case For 10 Seconds | | 260 | °C |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

| PARAMETER | SYMBOL | RATINGS | UNIT |
|---------------------|---------------|---------|------|
| Junction to Ambient | θ_{JA} | 42.3 | °C/W |
| Junction to Case | θ_{JC} | 12 | °C/W |

■ RECOMMENDED OPERATING CONDITIONS

| PACKAGE | SYMBOL | MIN | TYP | MAX | UNIT |
|--------------------------------|---|-----|-----|--------------|----------|
| Supply Voltage | V_{DD} | 2.5 | | 5.5 | V |
| High-Level Input Voltage | SHUTDOWN V_{IH} | 2 | | | V |
| Low-Level Input Voltage | SHUTDOWN V_{IL} | | | 0.8 | V |
| Common-Mode Input Voltage | V=2.5V, 5.5V, CMRR≤-60dB V_{IC} | 0.5 | | $V_{DD}-0.8$ | V |
| Operating Free-Air Temperature | T_A | -40 | | 85 | °C |
| Load Impedance | Z_L | 6.4 | 8 | | Ω |

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, Gain=1V/V, unless otherwise noted)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--------------|--|---------------|------|------|---------------|
| Output Offset Voltage (Measured Differentially) | $ V_{OO} $ | $V_I=0V$, $V_{DD}=2.5V\sim 5.5V$ | | | 9 | mV |
| Power Supply Rejection Ratio | PSRR | $V_{DD}=2.5V\sim 5.5V$ | | -90 | -70 | dB |
| Common Mode Rejection Ratio | CMRR | $V_{DD}=3.6V\sim 5.5V$, $V_{IC}=0.5V\sim V_{DD}-0.8$ | | -70 | -65 | dB |
| | | $V_{DD}=2.5V$, $V_{IC}=0.5V\sim 1.7V$ | | -62 | -55 | |
| Low-Level Output Voltage | V_{OL} | $R_L=8\Omega$, $V_{IN+}=V_{DD}$, $V_{IN-}=0V$ or $V_{IN+}=0V$, $V_{IN-}=V_{DD}$ | $V_{DD}=5.5V$ | 0.30 | 0.46 | V |
| | | | $V_{DD}=3.6V$ | 0.22 | | |
| | | | $V_{DD}=2.5V$ | 0.19 | 0.26 | |
| High-Level Output Voltage | V_{OH} | $R_L=8\Omega$, $V_{IN+}=V_{DD}$, $V_{IN-}=0V$ or $V_{IN+}=0V$, $V_{IN-}=V_{DD}$ | $V_{DD}=5.5V$ | 4.8 | 5.12 | V |
| | | | $V_{DD}=3.6V$ | | 3.28 | |
| | | | $V_{DD}=2.5V$ | 2.1 | 2.24 | |
| High-Level Input Current | $ I_{IH} $ | $V_{DD}=5.5V$, $V_I=5.8V$ | | | 1.2 | μA |
| Low-Level Input Current | $ I_{IL} $ | $V_{DD}=5.5V$, $V_I=-0.3V$ | | | 1.2 | μA |
| Supply Current | I_{DD} | SHUTDOWN=2V, $V_{DD}=2.5V\sim 5.5V$, No Load | | 1.7 | 2 | mA |
| Supply Current in Shutdown Mode | $I_{DD(SD)}$ | SHUTDOWN=0.8V, $V_{DD}=2.5V\sim 5.5V$, No Load | | 0.01 | 0.9 | μA |

■ OPERATING CHARACTERISTICS (T_A=25°C, Gain=1V/V, R_L=8Ω)

| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|--------------------------------------|------------------|--|---|------|------|-----|-------------------|
| Output Power | P _O | THD+N=1%, f=1kHz | V _{DD} =5V | | 1.25 | | W |
| | | | V _{DD} =3.6V | | 0.63 | | W |
| | | | V _{DD} =2.5V | | 0.3 | | W |
| Total Harmonic Distortion Plus Noise | THD+N | V _{DD} =5V, P _O =1W, f=1kHz | | | 0.06 | | % |
| | | V _{DD} =3.6V, P _O =0.5W, f=1kHz | | | 0.07 | | |
| | | V _{DD} =2.5V, P _O =200mW, f=1kHz | | | 0.08 | | |
| Supply Ripple Rejection Ratio | K _{SVR} | C _(BYPASS) =0.47μF, V _{DD} =3.6V~5.5V, Inputs Ac-Grounded with C _I =2μF | f=217Hz~2kHz, V _{RIPPLE} =200mV _{PP} | | -87 | | dB |
| | | C _(BYPASS) =0.47μF, V _{DD} =2.5V~3.6V, Inputs Ac-Grounded with C _I =2μF | f=217Hz~2kHz, V _{RIPPLE} =200mV _{PP} | | -82 | | dB |
| | | C _(BYPASS) =0.47μF, V _{DD} =2.5V~5.5V, Inputs Ac-Grounded with C _I =2μF | f=40Hz~20kHz, V _{RIPPLE} =200mV _{PP} | | ≤-74 | | dB |
| Signal-To-Noise Ratio | SNR | V _{DD} =5V, P _O =1W | | | 104 | | dB |
| Output Voltage Noise | V _N | f=20Hz~20kHz | No Weighting | | 17 | | μV _{RMS} |
| | | | A Weighting | | 13 | | |
| Common Mode Rejection Ratio | CMRR | V _{DD} =2.5V~5.5V, Resistor Tolerance=0.1%, Gain=4V/V, V _{ICM} =200mV _{PP} | f=20Hz~1kHz | | ≤-85 | | dB |
| | | | f=20Hz~20kHz | | ≤-74 | | dB |
| Input Impedance | Z _I | | | | 2 | | MΩ |
| Output Impedance | Z _O | Shutdown Mode | | >10k | | | |
| Shutdown Attenuation | | f=20Hz~20kHz, R _F =R _I =20kΩ | | | -80 | | dB |

■ TYPICAL APPLICATION CIRCUIT

Table 1. Typical Component Values

| COMPONENT | VALUE | UNIT |
|-------------------------|-------|------------|
| R_I | 10 | k Ω |
| R_F | 10 | k Ω |
| $C_{(BYPASS)}$ (Note 1) | 0.22 | μ F |
| C_S | 1 | μ F |
| C_I | 0.22 | μ F |

Note: 1. $C_{(BYPASS)}$ is optional




Figure 1. Typical Differential Input Application Schematic




Figure 2. Differential Input Application Schematic Optimized With Input Capacitors

■ TYPICAL APPLICATION CIRCUIT(Cont.)




Figure 3. Single-Ended Input Application Schematic

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.