




1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Vss	Vdd	V0	Vout	A0	E1	E2	D0	D1	NC	NC	D2	D3	D4	D5	D6	D7	NC	A	K

DETAIL A:



- NOTES:
- 1.DISPLAY TYPE: STN/Y-G MODE
 - 2.VIEWING DIRECTION: 12:00
 - 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
 - 4.DRIVE METHOD: 1/32 DUTY 1/6 BIAS
 - 5.LCD OPERATING VOLTAGE: 5.9V
 - 6.OPERATING TEMP: -20°C~+70°C
 - 7.STORAGE TEMP: -30°C~+80°C
 - 8.CONTROLLER: SED1520DA
 - 9.BACKLIGHT TYPE: LED
 - 10.BEZEL IS TO BE PAINTED BLACK
 - 11.UNMARKED TOLERANCES: ±0.3mm

 TIAN-MA MICROELECTRONICS CO. 22/F., HANGOU Building, Shennan Road, Central, Shenzhen, China		
DRAWN BY: 文炳明-01	TITLE: TM12232EBCWU6	
CHECKED BY: 张林	DWG NO: G-1	
APPROVED BY: 张林	DWG NAME: TM12232EBCWU6-1	
CONFIRMED BY: 张林	SHEET NO: 01	SCALE: 1:1 UNIT: mm