



COPPER CONDUCTOR(N/mm):
40/0.162±0.005 or Substitute

PVC INSULATION AVERAGE
THICKNESS: 0.38mm
ID: 2.10±0.1mm

DENIER:1500d

PVC JACKET AVERAGE
THICKNESS: 0.76mm
OD: 6.30 ±0.2mm

Material:

- SVT 3x18AWG(0.824MM²) VW-1 UnShielded, 60° 300V
- Jacket Color: Black
- E- Green; L- Black; N- White

Electrical :

- 100% Open & Short Testing
- Insulation Resistance : 100meg-ohm(Min.)
- Voltage : 500V DC / 1 Min.

Unit: mm



Scale	Free					Date	Name	
TOLERANCE					Drawn	27.12.11	Chappell	
X.	±X				Approved	21.06.13	Groll	
X.X	±X							
X.XX	±X							
DIM	TOL							
X.°	±X°	①	Updated all information	21.06.13				Wilson
X.X°	±X°							
Angle	TOL	Id.	Modification	Date				Name

Title	
Power cord - IEC Extension	
SVT, 18AWG, 60°C, Unshielded, 2 meters	
ASSMANN WSW-No.	
AK500-OE-11-2-R	
Drawing-No.	
	rev01
Replace	Sheet
	1/1