


STANDARD TRIACS

FEATURES

- $I_{T(RMS)} = 4A$
- $V_{DRM} = 400V$ to $800V$
- $I_{GT} \leq 25mA$



DESCRIPTION

The Z0410xE/F series of triacs uses a high performance TOP GLASS PNPN technology. These parts are intended for general purpose switching and phase control applications.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value		Unit
$I_{T(RMS)}$	RMS on-state current (360° conduction angle)	Z0410xE/F	$T_c = 75^\circ C$	4	A
		Z0410xF	$T_a = 25^\circ C$	0.95	
I_{TSM}	Non repetitive surge peak on-state current (T_j initial = $25^\circ C$)	$tp = 8.3$ ms	22	A	
		$tp = 10$ ms	20		
I^2t	I^2t Value for fusing	$tp = 10$ ms	2	A^2s	
dI/dt	Critical rate of rise of on-state current $I_G = 50$ mA $dI/dt = 0.1$ A/ μs .	Repetitive $F = 50$ Hz	10	$A/\mu s$	
		Non Repetitive	50		
T_{stg} T_j	Storage and operating junction temperature range	-40, +150 -40, +125			$^\circ C$
TI	Maximum lead temperature for soldering during 10s at 4.5mm from case	260			$^\circ C$

Symbol	Parameter	Voltage				Unit
		D	M	S	N	
V_{DRM} V_{RRM}	Repetitive peak off-state voltage $T_j = 125^\circ C$	400	600	700	800	V

Z0410xE/F

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
R _{th(j-a)}	Junction to ambient	80	°C/W
		100	
R _{th(j-c)}	Junction to case for D.C	10	°C/W
R _{th(j-c)}	Junction to case for A.C 360° conduction angle (F=50Hz)	7.5	°C/W

GATE CHARACTERISTICS (maximum values)

P_{G (AV)}= 0.2 W P_{GM} = 3 W (tp = 20 μs) I_{GM} = 1.2 A (tp = 20 μs)

ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions	Quadrant		Sensitivity	Unit
				10	
I _{GT}	V _D =12V (DC) R _L =33Ω	T _j = 25°C	I-II-III-IV	MAX	25 mA
V _{GT}	V _D =12V (DC) R _L =33Ω	T _j = 25°C	I-II-III-IV	MAX	1.5 V
V _{GD}	V _D =V _{DRM} R _L =3.3kΩ	T _j = 125°C	I-II-III-IV	MIN	0.2 V
t _{GT}	V _D =V _{DRM} I _G = 40mA I _T = 5.5A dI _G /dt = 0.5A/μs	T _j = 25°C	I-II-III-IV	TYP	2 μs
I _H *	I _T = 50 mA Gate open	T _j = 25°C		MAX	25 mA
I _L	I _G = 1.2 I _{GT}	T _j = 25°C	I-III-IV	TYP	25 mA
			II	TYP	50 mA
V _{TM} *	I _{TM} = 5.5A tp= 380μs	T _j = 25°C		MAX	2 V
I _{DRM} I _{RRM}	V _D = V _{DRM} V _R = V _{RRM}	T _j = 25°C		MAX	5 μA
		T _j = 110°C		MAX	200 μA
dV/dt*	VD=67%V _{DRM} Gate open	T _j = 110°C	MIN	200 V/μs	
			TYP	400 V/μs	
(dV/dt)c*	(dI/dt)c = 1.8 A/ms	T _j = 110°C		MIN	5 V/μs

* For either polarity of electrode A₂ voltage with reference to electrode A₁

ORDERING INFORMATION




Fig.1 : Maximum RMS power dissipation versus RMS on-state current.




Fig.3 : Maximum RMS power dissipation versus RMS on-state current.




Fig.5 : RMS on-state current versus case temperature (TO202-1).




Fig.2 : Correlation between maximum RMS power dissipation and maximum allowable temperature (T_{amb} and T_{case}) for different thermal resistances heatsink + contact (TO202-1).




Fig.4 : Correlation between maximum RMS power dissipation and maximum allowable temperature (T_{amb} and T_{case}) (TO202-2).





Fig.6 : RMS on-state current versus case temperature (TO202-2).



Z0410xE/F

Fig.6 : Relative variation of thermal impedance versus pulse duration (TO202-1).




Fig.7 : Relative variation of thermal impedance junction to ambient versus pulse duration (TO202-2).




Fig.9 : Relative variation of gate trigger current and holding current versus junction temperature.




Fig.11 : Non repetitive surge peak on-state current for a sinusoidal pulse with width : $tp \leq 10\text{ms}$, and corresponding value of I^2t .




Fig.10 : Non repetitive surge peak on-state current versus number of cycles.





Fig.12 : On-state characteristics (maximum values).



PACKAGE MECHANICAL DATA
TO202-1 (Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Typ.	Min.	Max.	Typ.	Min.	Max.
A			10.1			0.398
B	13.7			0.540		
C	7.3			0.287		
D	10.5			0.413		
F			1.5			0.059
G	3.2			0.126		
H	0.51			0.020		
I		3.16	3.20		0.124	0.126
J	1.5			0.059		
M	4.5			0.177		
N			5.3			0.209
N1	2.54			0.100		
O			1.4			0.055
P			0.7			0.028

Marking : type number

Weight : 1.4 g

Z0410xE/F

PACKAGE MECHANICAL DATA TO202-2 (Plastic)

REF.	DIMENSIONS					
	Millimeters			Inches		
	Typ.	Min.	Max.	Typ.	Min.	Max.
A			10.1			0.398
B	1.2			0.047		
C	7.3			0.287		
D	10.5			0.413		
E	7.4			0.290		
F			1.5			0.059
H	0.51			0.020		
J	1.5			0.059		
M	4.5			0.177		
N			5.3			0.209
N1	2.54			0.100		
O			1.4			0.055
P			0.7			0.028

Marking : type number

Weight : 1.0 g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.