


SOT-23 Plastic-Encapsulate Diodes

CESD5V0AP ESD Protection Diode

DESCRIPTION

The CESD5V0AP is designed to protect voltage sensitive components from ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed to ESD. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space is at a premium.

SOT-23



FEATURES

- Stand-off Voltage: 5.0 V
- Low Leakage
- Response Time is Typically < 1 ns
- ESD Rating of Class 3 (> 16 kV) Per Human Body Model
- IEC61000-4-2 Level 4 ESD Protection
- These are Pb-Free Devices

Maximum Ratings @Ta=25°C

Parameter	Symbol	Limit	Unit
IEC61000-4-2(ESD) Air Contact		±15 ±8.0	KV
ESD voltage per human body model		16	KV
Total power dissipation on FR-5 board (Note 1)	P_D	225	mW
Thermal resistance junction-to-ambient	$R_{\theta JA}$	556	°C/W
Lead solder temperature -maximum (10 second duration)	T_L	260	°C
Junction and storage temperature range	T_j, T_{stg}	-55 ~ +150	°C

Stresses exceeding maximum ratings may damage the device. Maximum ratings are stress ratings only.


Functional operation above the recommended. Operating conditions is not implied. Extended exposure to stresses above the recommended operating conditions may affect device reliability.

Note 1. FR-5 = 1.0 x 0.75 x 0.62 in.

ELECTRICAL CHARACTERISTICS (Ta= 25°C unless otherwise noted)

UNIDIRECTIONAL (Circuit tied to Pins 1 and 3 or 2 and 3)

Symbol	Parameter
I _{PP}	Maximum Reverse Peak Pulse Current
V _C	Clamping Voltage @ I _{PP}
V _{RWM}	Working Peak Reverse Voltage
I _R	Maximum Reverse Leakage Current @ V _{RWM}
V _{BR}	Breakdown Voltage @ I _T
I _T	Test Current
I _F	Forward Current
V _F	Forward Voltage @ I _F
P _{pk}	Peak Power Dissipation
C	Max. Capacitance @V _R =0 and f =1MHz



ELECTRICAL CHARACTERISTICS (Ta = 25°C unless otherwise noted, V_F = 0.9 V Max. @ I_F = 10mA for all types)

Device*	Device Marking	V _{RWM} (V)	I _R (μ A) @ V _{RWM}	V _{BR} (V) @ I _T (Note 2)		I _T mA	V _C @I _{PP} =1 A	Max I _{PP} +	P _{pk} + (W)	C (pF) Pin 1 to 3
		Max	Max	Min	Max		V	A	Max	Typ
CESD5V0AP	5M	5	10	6.2	7.3	1.0	9.8	12	300	110

*Other voltages available upon request.

+Surge current waveform per Figure 3

Note 2. V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C.