

4-Lines, Uni-directional, Low Capacitance Transient Voltage Suppressors

Descriptions

The ESD5305F is a low capacitance TVS (Transient Voltage Suppressor) array designed to protect high speed data interfaces. It has been specifically designed to protect sensitive electronic components which are connected to data and transmission lines from over-stress caused by ESD (Electrostatic Discharge).

The ESD5305F incorporates four pairs of low capacitance steering diodes plus a TVS diode.

The ESD5305F may be used to provide ESD protection up to ±30kV (contact discharge) according to IEC61000-4-2, and withstand peak pulse current up to 6A (8/20µs) according to IEC61000-4-5.


The ESD5305F is available in SOT23-6L package. Standard products are Pb-free and Halogen-free.

Features


- Reverse stand-off voltage: 5V max.
- Transient protection for each line according to IEC61000-4-2 (ESD): ±30kV (contact discharge)
IEC61000-4-5 (surge): 6A (8/20µs)
- Low capacitance: $C_{I/O-GND} = 0.65\text{pF typ. (Vcc = floated)}$
 $C_{I/O-GND} = 0.35\text{pF typ. (Vcc = 5V)}$
- Ultra-low leakage current: $I_R < 1\text{nA typ.}$
- Low clamping voltage: $V_{CL} = 16.5\text{V @ } I_{PP} = 16\text{A (TLP)}$
- Solid-state silicon technology

Applications


- USB 2.0
- HDMI 1.3
- SATA and eSATA
- DVI
- IEEE 1394
- PCI Express
- Portable Electronics
- Notebooks



SOT23-6L



Circuit diagram



5305 = Device code
YY = Year code
WW = Week code

Marking & Pin configuration (Top View)


Order information

Device	Package	Shipping
ESD5305F-6/TR	SOT23-6L	3000/Tape&Reel

Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	84	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{pp}	6	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	
Operation junction temperature	T_J	125	$^{\circ}C$
Lead temperature	T_L	260	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

Electrical characteristics ($T_A = 25^{\circ}C$, unless otherwise noted)



Definitions of electrical characteristics


Electrical characteristics (T_A = 25°C, unless otherwise noted)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V _{RWM}				5.0	V
Reverse leakage current	I _R	V _{RWM} = 5V		<1	50	nA
Reverse breakdown voltage	V _{BR}	I _{BR} = 1mA	7.0	8.0	9.0	V
Forward voltage	V _F	I _F = 10mA	0.6	0.9	1.2	V
Clamping voltage ¹⁾	V _{CL}	I _{PP} = 16A, t _p = 100ns		16.5		V
Dynamic resistance ¹⁾	R _{DYN}			0.45		Ω
Clamping voltage ²⁾	V _{CL}	I _{PP} = 1A, t _p = 8/20μs			10	V
		I _{PP} = 6A, t _p = 8/20μs			14	V
Junction capacitance	C _{I/O - GND}	V _R = 0V, f = 1MHz, V _{CC} = floated, Any I/O to GND		0.65	1.0	pF
		V _R = 0V, f = 1MHz, V _{CC} = 5V, Any I/O to GND		0.35	0.50	pF
	C _{I/O - I/O}	V _R = 0V, f = 1MHz, Any I/O to I/O		0.35	0.50	pF


Notes:

- 1) TLP parameter: Z₀ = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
- 2) Non-repetitive current pulse, according to IEC61000-4-5.


Typical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)




8/20 μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current



Capacitance vs. Reverse voltage




Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature


Typical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)



ESD clamping
(+8kV contact discharge per IEC61000-4-2)




ESD clamping
(-8kV contact discharge per IEC61000-4-2)



TLP Measurement

Package outline dimensions

SOT23-6L



Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	--	--	1.25
A1	0	--	0.15
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.36	--	0.50
b1	0.36	0.38	0.45
c	0.14	--	0.20
c1	0.14	0.15	0.16
D	2.826	2.926	3.026
E	2.60	2.80	3.00
E1	1.526	1.626	1.726
e	0.90	0.95	1.00
e1	1.80	1.90	2.00
L	0.35	0.45	0.60
L1	0.59REF		
L2	0.25BSC		
R	0.10	--	--
R1	0.10	--	0.20
θ	0°	--	8°
θ1	3°	5°	7°
θ2	6°	--	14°