



GSD

GSD

REVISIONS	
ISSUE	CHANGES
0	ER 36034 KH 01/25/95
1	CN 37803 A HVN 04/12/99
2	CN 38864 E JPK 06/03/03
3	CN 38932 A TML 09/29/03

7702-12

- NOTES:
- FOR USE WITH 740 CABLE GROUP (BELDEN 9232).
  - FOR CABLING INSTRUCTIONS SEE 3-499.
  - MATERIALS:  
 INSULATORS-TEFLON, ASTM-D-4894  
 LOCKWASHER: PHOSPHOR BRONZE, QQ-B-750  
 CAP: VINYL  
 GASKETS-SILICONE RUBBER, ZZ-R-765  
 OUTER CONTACT SPRING } BER. COP., ASTM-B-196.  
 CONTACT F  
 ALL OTHER METAL PARTS-BRASS, ASTM-B16
  - FINISHES:  
 OUTER CONTACT SPRING } GOLD PLATE PER MIL-G-45204  
 CENTER CONTACT  
 WASHERS  
 BRAID CLAMP } SILVER PLATE PER QQ-S-365  
 SLEEVE  
 ALL OTHER METAL PARTS-KINGS TARNISH RESISTANT NICKEL FINISH (TR-5)
  - ELECTRICAL CHARACTERISTIC:  
 NOMINAL IMPEDANCE-75 OHMS

7702-12SD

SCALE 2:1	
APPROX SURFACE AREA	
WAS: E-18688	
USED ON	
REF:	
JACK, ANGLE, BULKHEAD, TRI-LOC	
DRAWN KH	DATE 01/25/95
DESIGN GA	DATE 01/26/95
APPR. DW	DATE 09/11/95

**KINGS**  
ELECTRONICS CO., INC.  
ROCK HILL, SOUTH CAROLINA 29730

7702-12