

RF AMPLIFIER

MODEL *BXMP1037*

Available as: BXMP1037, SMA Connectorized Housing

www.DataSheet4U.com

Features

- High Third Intercept: +45 dBm Typical
- High Output Power: +31 dBm Typical
- Operating Temp. -20 °C to +70 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta = 25 °C	MIN/MAX Ta = -20 °C to +70 °C
Frequency	1000 - 2000 MHz	1000 - 2000 MHz
Gain (dB)	19.0	17.0
Power @ 1 dB Comp. (dBm)	+31	+30 Min.
Reverse Isolation (dB)	-24	-23 Max.
VSWR In	1.5:1	2.0:1 Max.
Out	1.5:1	2.0:1 Max.
Noise Figure (dB)	5.0	6.0 Max.
Power Vdc	+15	+15
mA	450	500 Max.

Note: Care should always be taken to effectively ground the case of each unit.







Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point+60 dBm (Typ.)
 Second Order Two Tone Intercept Point+54 dBm (Typ.)
 Third Order Two Tone Intercept Point+45 dBm (Typ.)

Maximum Ratings

Ambient Operating Temperature-55°C to +100 °C
 Storage Temperature-62°C to +125 °C
 Case Temperature+125 °C
 DC Voltage+18 Volts
 Continuous RF Input Power+20 dBm
 Short Term RF Input Power 500 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Typical Performance Data



Legend ——— +25 °C - - - +70 °C -20 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev.
11/16/07

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001

www.DataSheet4U.com