


**P-Channel Logic Level Enhancement Mode Field Effect Transistor****PRODUCT SUMMARY**

V _{DSS}	I _D	R _{DS(ON)} (mΩ) Max
-40V	-32A	16 @ V _{GS} =-10V
		30 @ V _{GS} =-4.5V

FEATURES

- Super high dense cell design for low R_{DS(ON)}.
- Rugged and reliable.
- Surface Mount Package.

**ABSOLUTE MAXIMUM RATINGS (T_C=25°C unless otherwise noted)**

Symbol	Parameter	Limit	Units
V _{DS}	Drain-Source Voltage	-40	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Drain Current-Continuous ^{a e}	T _C =25°C	-32
		T _C =70°C	-25.6
I _{DM}	-Pulsed ^b	-94	A
E _{AS}	Single Pulse Avalanche Energy ^d	121	mJ
P _D	Maximum Power Dissipation	T _C =25°C	42
		T _C =70°C	27
T _J , T _{STG}	Operating Junction and Storage Temperature Range	-55 to 150	°C

THERMAL CHARACTERISTICS

R _{θJC}	Thermal Resistance, Junction-to-Case	3	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient	50	°C/W

STU437S

STD437S

Ver 1.0

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =-250uA	-40			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-32V , V _{GS} =0V			1	uA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V , V _{DS} =0V			±100	nA
ON CHARACTERISTICS						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250uA	-1	-1.9	-3	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-10V , I _D =-16A		13	16	m ohm
		V _{GS} =-4.5V , I _D =-12A		22	30	m ohm
g _{FS}	Forward Transconductance	V _{DS} =-10V , I _D =-16A		32		S
DYNAMIC CHARACTERISTICS ^c						
C _{ISS}	Input Capacitance	V _{DS} =-20V, V _{GS} =0V f=1.0MHz		2200		pF
C _{OSS}	Output Capacitance			244		pF
C _{RSS}	Reverse Transfer Capacitance			180		pF
SWITCHING CHARACTERISTICS ^c						
t _{D(ON)}	Turn-On Delay Time	V _{DD} =-20V I _D =-1.0A		36		ns
t _r	Rise Time			32		ns
t _{D(OFF)}	Turn-Off Delay Time	V _{GS} =-10V R _{GEN} = 6 ohm		109		ns
t _f	Fall Time			28		ns
Q _g	Total Gate Charge	V _{DS} =-20V, I _D =-16A, V _{GS} =-10V		37		nC
Q _{gs}	Gate-Source Charge	V _{DS} =-20V, I _D =-16A, V _{GS} =-10V		4.3		nC
Q _{gd}	Gate-Drain Charge			12		nC
DRAIN-SOURCE DIODE CHARACTERISTICS						
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S = -4A		-0.8	-1.3	V
Notes						
a.Surface Mounted on FR4 Board,t < 10sec.						
b.Pulse Test:Pulse Width < 300us, Duty Cycle < 2%.						
c.Guaranteed by design, not subject to production testing.						
d.Starting T _J =25°C,L=0.5mH,V _{DD} = 20V .(See Figure13)						
e.Drain current limited by maximum junction temperature.						

Sep,09,2013

STU437S STD437S

Ver 1.0




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature

Sep,09,2013

STU437S STD437S

Ver 1.0




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11. switching characteristics





Figure 12. Maximum Safe Operating Area

Sep,09,2013


STU437S STD437S

Ver 1.0



Uncamped Inductive Test Circuit

Figure 13a.



Unclamped Inductive Waveforms

Figure 13b.





Figure 14. Normalized Thermal Transient Impedance Curve

Sep,09,2013

STU437S STD437S

Ver 1.0

PACKAGE OUTLINE DIMENSIONS




Sep,09,2013

STU437S STD437S

Ver 1.0

TO-252



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.100	2.500	0.083	0.098
A1	0.000	0.200	0.000	0.008
b	0.400	0.889	0.016	0.035
b1	0.770	1.140	0.030	0.045
b2	4.800	5.460	0.189	0.215
C	0.400	0.600	0.016	0.024
D	5.300	6.223	0.209	0.245
D1	4.900	5.515	0.193	0.217
E	6.300	6.731	0.248	0.265
E1	4.400	5.004	0.173	0.197
e	2.290 REF		0.090 BSC	
H	8.900	10.400	0.350	0.409
L	1.397	1.770	0.055	0.070
L1	2.743 REF.		0.108 REF.	
L2	0.508 REF.		0.020 REF.	
L3	0.890	1.700	0.035	0.067
L4	0.500	1.100	0.020	0.043
theta	0°	10°	0°	10°
theta1	7° REF.		7° REF.	


Sep,09,2013

STU437S STD437S


Ver 1.0

TO-251 Tube/TO-252 Tape and Reel Data

TO-251 Tube




TO-252 Carrier Tape



UNIT:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
TO-252 (16 mm)	6.96 ±0.1	10.49 ±0.1	2.79 ±0.1	φ 2	φ 1.5 +0.1 - 0	16.0 ±0.3	1.75 ±0.1	7.5 ±0.15	8.0 ±0.1	4.0 ±0.1	2.0 ±0.15	0.3 ±0.05

TO-252 Reel



UNIT:mm


TAPE SIZE	REEL SIZE	M	N	W	T	H	K	S	G	R	V
16 mm	φ 330	φ 330 ± 0.5	φ 97 ± 1.0	17.0 + 1.5 - 0	2.2	φ 13.0 + 0.5 - 0.2	10.6	2.0 ±0.5	---	---	---

Sep,09,2013

STU437S STD437S

Ver 1.0

TOP MARKING DEFINITION



Sep,09,2013

STU437S STD437S

TOP MARKING DEFINITION

