



# America Semiconductor

## Silicon Power Schottky Diode

1N5826 thru  
1N5828R

$V_{RRM} = 20\text{ V} - 40\text{ V}$


$I_F = 15\text{ A}$

### Features


- High Surge Capability
- Types up to 40V  $V_{RRM}$

### Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



DO-5 Package



### Maximum ratings, at $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	1N5826 (R)	1N5827 (R)	1N5828 (R)	Unit
Repetitive peak reverse voltage	$V_{RRM}$		20	30	40	V
RMS reverse voltage	$V_{RMS}$		14	21	28	V
DC blocking voltage	$V_{DC}$		20	30	40	V
Continuous forward current	$I_F$	$T_C \leq 100\text{ }^\circ\text{C}$	15	15	15	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25\text{ }^\circ\text{C}$ , $t_p = 8.3\text{ ms}$	500	500	500	A
Operating temperature	$T_j$		-65 to 150	-65 to 150	-65 to 150	$^\circ\text{C}$
Storage temperature	$T_{stg}$		-65 to 175	-65 to 175	-65 to 175	$^\circ\text{C}$

### Electrical characteristics, at $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	1N5826 (R)	1N5827 (R)	1N5828 (R)	Unit
Diode forward voltage	$V_F$	$I_F = 15\text{ A}$ , $T_j = 25\text{ }^\circ\text{C}$	0.44	0.47	0.5	V
Reverse current	$I_R$	$V_R = 20\text{ V}$ , $T_j = 25\text{ }^\circ\text{C}$ $V_R = 20\text{ V}$ , $T_j = 125\text{ }^\circ\text{C}$	10 250	10 250	10 250	mA

### Thermal characteristics

Thermal resistance, junction - case	$R_{thJC}$		1.8	1.8	1.8	$^\circ\text{C/W}$
-------------------------------------	------------	--	-----	-----	-----	--------------------



