

## isc Triacs


## BTA08-600A

## FEATURES

- With TO-220AB insulated package
- Suitable for general purpose applications where gate high sensitivity is required. Application on 4Q such as phase control and static switching.

## ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	MIN	UNIT
$V_{DRM}$	Repetitive peak off-state voltage	600	V
$V_{RRM}$	Repetitive peak reverse voltage	600	V
$I_{T(RMS)}$	RMS on-state current (full sine wave) $T_j=105^\circ\text{C}$	8	A
$I_{TSM}$	Non-repetitive peak on-state current $t_p=20\text{ms}$	80	A
$T_j$	Operating junction temperature	110	°C
$T_{stg}$	Storage temperature	-45~150	°C
$R_{th(j-c)}$	Thermal resistance, junction to case	2.5	°C/W
$R_{th(j-a)}$	Thermal resistance, junction to ambient	60	°C/W

ELECTRICAL CHARACTERISTICS (T<sub>c</sub>=25°C unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT	
$I_{RRM}$	Repetitive peak reverse current	$V_R=V_{RRM}$ , $V_R=V_{RRM}$ , $T_j=110^\circ\text{C}$	0.01 0.5	mA	
$I_{DRM}$	Repetitive peak off-state current	$V_D=V_{DRM}$ , $V_D=V_{DRM}$ , $T_j=110^\circ\text{C}$	0.01 0.5	mA	
$I_{GT}$	Gate trigger current	I	$V_D=12\text{V}$ ; $R_L=30\ \Omega$	10	mA
		II			
		III			
		IV			
$I_H$	Holding current	$I_{GT}=0.1\text{A}$ , Gate Open	25	mA	
$V_{GT}$	Gate trigger voltage all quadrant	$V_D=12\text{V}$ ; $R_L=30\ \Omega$	1.5	V	
$V_{TM}$	On-state voltage	$I_T=11\text{A}$ ; $t_p=380\ \mu\text{s}$	1.75	V	