


GLASS PASSIVATED BRIDGE RECTIFIERS

REVERSE VOLTAGE - 600 Volts
FORWARD CURRENT - 20 Amperes

FEATURES

- Ideal for printed circuit board
- Low forward voltage drop, high current capability
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- The plastic material has UL flammability classification 94V-0



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	4GBJ2006L	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	600	V
Maximum RMS Voltage	V _{RMS}	420	V
Maximum DC Blocking Voltage	V _{DC}	600	V
Maximum Average Forward Rectified Current @ T _c =100°C	I _(AV)	20	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I _{FSM}	250	A
Maximum Forward Voltage at 10A DC	V _F	0.92	V
I ² t Rating for Fusing (t<8.3ms)	I ² t	260	A ² s
Maximum DC Reverse Current @ T _J =25°C	I _R	10.0	μA
at Rated DC Blocking Voltage @ T _J =125°C		500	
Operating Temperature Range	T _J	127	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXMUN NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL FORWARD CHARACTERISTICS

