


2A SURFACE MOUNT SCHOTTKY BRIDGE
FEATURES:

- Reverse Voltage - 40 to 200 V
- Forward Current - 2 A
- High Surge Current Capability
- Designed for Surface Mount Application

PINNING

PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



ABS/LBF Package

MECHANICAL DATA

- Case: ABS/LBF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 88mg 0.0031oz

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	TB24S	TB26S	TB28S	TB210S	TB220S	Units					
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	40	60	80	100	200	V					
Maximum RMS voltage	V _{RMS}	28	42	56	70	140	V					
Maximum DC Blocking Voltage	V _{DC}	40	60	80	100	200	V					
Maximum Average Forward Rectified Current	I _{F(AV)}	2.0					A					
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	50		40		A						
Max Instantaneous Forward Voltage at 2A	V _F	0.55	0.70	0.85			V					
Maximum DC Reverse Current T _a = 25°C at Rated DC Reverse Voltage T _a = 100°C	I _R	0.5 10		0.3 5		mA						
Typical Junction Capacitance ¹⁾	C _j	220	80			pF						
Typical Thermal Resistance ²⁾	R _{θJA}	70				°C/W						
Operating Junction Temperature Range	T _j	-55 ~ +125				°C						
Storage Temperature Range	T _{stg}	-55 ~ +150				°C						

Note: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad.

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




PACKAGE OUTLINE

Plastic surface mounted package; 4 leads

ABS/LBF



The recommended mounting pad size



Marking

Type number	Marking code
TB24S	TB24S
TB26S	TB26S
TB28S	TB28S
TB210S	TB210S
TB220S	TB220S

Diagram of the package showing the marking code TBxxS.