


HERMETIC SURFACE MOUNT FIXED VOLTAGE POSITIVE REGULATORS



**Three Terminal, Fixed Voltage, 1.5 Amp
Precision Positive Regulators In Hermetic
Surface Mount Package**

FEATURES

- Hermetic Surface Mount Package
- Output Voltages: +5V, +12V, +15V
- Output Voltages Set Internally To $\pm 1\%$
- Built-In Thermal Overload Protection
- Short Circuit Current Limiting
- Product Is Available Hi-Rel Screened

DESCRIPTION

These three terminal positive regulators are supplied in a hermetically sealed surface mount package. All protective features are designed into the circuit including thermal shutdown, current limiting and safe-area control. With heat sinking, they can deliver over 1.5 amps of output current. These units feature internally trimmed output voltages to $\pm 1\%$ of nominal voltage. Standard voltages are +5V, +12V, and +15V. These units are ideally suited for Military applications where a hermetic surface mount package is required.

ABSOLUTE MAXIMUM RATINGS

Input to Output Voltage Differential.....+35 V

Operating Junction Temperature Range.....-55°C to + 150°C

Storage Temperature Range-55°C to + 150°C

Typical Power/Thermal Characteristics:

Rated Power @ 25°C

T_C.....17.5W

T_A.....3W

Thermal Resistance:

θ_{JC}3.5°C/W

θ_{JA} 42°C/W

Lead Temperature at Case (5 sec).....225°C

3.5

ELECTRICAL CHARACTERISTICS 5 Volt $V_{IN} = 10V$, $I_O = 500mA$, $-55^\circ C \leq T_A \leq 125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	4.92	5.08	V
		$V_{IN} = 7.5V$ to $20V$	•	4.85	mV
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 7.5V$ to $20V$		5	mV
		$V_{IN} = 8.0V$ to $12V$	•	12	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to $1.5Amp$	•	4	mV
		$I_O = 250mA$ to $750mA$	•	10	mV
Standby Current Drain	I_{SCD}			6	mA
			•	6.5	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 7.5V$ to $20V$	•	0.8	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to $1000mA$	•	0.5	mA
Dropout Voltage	V_{DO}	$T_A = 25^\circ C$, $\Delta V_{OUT} = 100mV$, $I_O = 1.0A$		2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$		1.5	A
Short Circuit Current (Note 2)	I_{BS}	$V_{IN} = 35V$	•	1.2	A
				2.8	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	$f = 120 Hz$, $\Delta V_{IN} = 10V$		66	dB
		(Note 3)	•	60	dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, $f = 10 Hz$ to $100KHz$		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, $t = 1000 hrs.$		75	mV

ELECTRICAL CHARACTERISTICS 12 Volt $V_{IN} = 19V$, $I_O = 500mA$, $-55^\circ C \leq T_A \leq 125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	11.88	12.12	V
		$V_{IN} = 14.5V$ to $27V$	•	11.64	mV
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 14.5V$ to $27V$		18	mV
		$V_{IN} = 16V$ to $22V$	•	50	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to $1.5Amp$	•	9	mV
		$I_O = 250mA$ to $750mA$	•	30	mV
Standby Current Drain	I_{SCD}			32	mA
			•	60	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 15V$ to $30V$	•	6.0	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to $1000mA$	•	6.5	mA
Dropout Voltage	V_{DO}	$\Delta V_{OUT} = 100mV$, $I_O = 1.0A$	•	2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$		1.5	A
Short Circuit Current (Note 2)	I_{BS}	$V_{IN} = 35V$	•	1.2	A
				2.8	A
Ripple Rejection	$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	$f = 120 Hz$, $\Delta V_{IN} = 10V$		61	dB
		(Note 3)	•	54	dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, $f = 10 Hz$ to $100KHz$		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	$\frac{\Delta V_{OUT}}{\Delta t}$	$T_A = 25^\circ C$, $t = 1000 hrs.$		120	mV

Notes:

- Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
 - Short Circuit protection is only assured up to $V_{IN} = 35V$.
 - If not tested, shall be guaranteed to the specified limits.
- The • denotes the specifications which apply over the full operating temperature range.

3.5

ELECTRICAL CHARACTERISTICS 15 Volt $V_{IN} = 23V$, $I_O = 500mA$, $-55^\circ C \leq T_A \leq 125^\circ C$ (unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Max.	Unit
Output Voltage	V_{OUT}	$T_A = 25^\circ C$	14.8	15.2	V
		$V_{IN} = 18.5V$ to 30V	• 14.6	15.4	V
Line Regulation (Note 1)	V_{RLINE}	$V_{IN} = 17.5V$ to 30V	• 20	50	mV
		$V_{IN} = 20V$ to 26V	• 15	25	mV
Load Regulation (Note 1)	V_{RLOAD}	$I_O = 5mA$ to 1.5 Amp	35	35	mV
		$I_O = 5mA$ to 1.0 Amp	• 75	75	mV
		$I_O = 250mA$ to 750 mA	• 21	45	mV
Standby Current Drain	I_{SCD}		• 6.0	6.5	mA
Standby Current Drain Change With Line	ΔI_{SCD} (Line)	$V_{IN} = 18.5V$ to 30V	• 0.8	0.8	mA
Standby Current Drain Change With Load	ΔI_{SCD} (Load)	$I_O = 5mA$ to 1000mA	• 0.5	0.5	mA
Dropout Voltage	V_{DO}	$T_A = 25^\circ C$, $\Delta V_{OUT} = 100mV$, $I_O = 1.0A$		2.5	V
Peak Output Current	$I_{O(pk)}$	$T_A = 25^\circ C$	1.5	3.3	A
Short Circuit Current (Note 2)	I_{DS}	$V_{IN} = 35V$	• 1.2	1.2	A
			• 2.8	2.8	A
Ripple Rejection	ΔV_{IN} ΔV_{OUT}	$f = 120$ Hz, $\Delta V_{IN} = 10V$	54	54	dB
		(Note 3)	• 52	52	dB
Output Noise Voltage (Note 3)	N_O	$T_A = 25^\circ C$, $f = 10$ Hz to 100KHz		40	$\mu V/V$ RMS
Long Term Stability (Note 3)	ΔV_{OUT} Δt	$T_A = 25^\circ C$, $t = 1000$ hrs.		150	mV


Notes:

- Load and Line Regulation are specified at a constant junction temperature. Pulse testing with low duty cycle is used. Changes in output voltage due to heating effects must be taken into account separately.
- Short Circuit protection is only assured up to $V_{IN} = 35V$.
- If not tested, shall be guaranteed to the specified limits.


The • denotes the specifications which apply over the full operating temperature range.

TYPICAL PERFORMANCE CHARACTERISTICS


PEAK OUTPUT CURRENT



DROPOUT VOLTAGE




RIPPLE REJECTION



3.5

TYPICAL APPLICATIONS


FIXED OUTPUT REGULATOR





* Increasing value of output capacitor improves system transient response

t Required only if regulator is located an appreciable distance from power supply filter.


CIRCUIT FOR INCREASING OUTPUT VOLTAGE




$$V_O = V_{xx} \left(1 + \frac{R_2}{R_1} \right) + I_Q R_2$$

HIGH OUTPUT CURRENT,
SHORT CIRCUIT PROTECTEDADJUSTABLE OUTPUT REGULATOR,
7 TO 30 VOLTS


PIN CONNECTION



Pin 1: In
Pin 2: Out
Pin 3: Ground



TOP VIEW



SIDE VIEW

BOTTOM VIEW