


Features

- Single / Common-Anode Configurations
- 4 Gram Minimum Lead Pull
- Oxide / Nitride / Polyimide Triple Passivation for High Reliability



Description

The planar beam lead PIN diodes provide low microwave capacitance with exceptional lead strength. The high beam strength offers the users superior assembly yield. The oxide / nitride / polyimide passivation offers high reliability with low reverse leakage current and high temperature performance.

Electrical Specifications¹: $T_A = +25^\circ\text{C}$

Part #	Configuration	Reverse Current (I_R)	Breakdown Voltage (V_{BR})	Junction Capacitance (C_J)	Series Resistance (R_S)	Lifetime (t)
		$V_R = 30\text{ V}$	$I_R = 10\ \mu\text{A}$	$V_R = 10\text{ V}, 15\text{ GHz}$	$I_F = 20\text{ mA}, 3\text{ GHz}$	
		nA	V	pF	Ω	ns
		Max.	Min.	Max.	Max.	Typ.
MPND4005-B15 MPND4005-B16	Single Common Anode	100	100	0.02	6.5	125


1. All devices available in a variety of packages. Consult factory for special version, high reliability screening or custom designs.

Absolute Maximum Ratings


Parameter	Absolute Maximum
Total Power Dissipation	250 mW @ 25°C, Derate linearly to 0 @ +175°C
Operating Temperature	-65°C to +175°C
Storage Temperature	-65°C to +200°C
Terminal Strength	4 grams minimum

Typical Performance Curves

Isolation vs. Frequency




Forward Resistance vs. Current




Outlines

B15



B16



MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.