

ISSUE 1; April 2016

Description

- Intended for applications requiring shock survivability to 10,000G (and higher), the surface-mount CXOXHG oscillator is a high-shock version of the CXOX oscillator. This oscillator consist of a CMOS compatible hybrid circuit and a state-of-the-art fundamental-mode crystal.
- SM1 Gold Plated (RoHS)
- SM5 Solder Dipped (RoHS)
- Please note that all data is only valid at 25°C unless otherwise stated.

Frequency Parameters

- | | |
|---------------------|-------------------------|
| Frequency | 1.0MHz to 160.0MHz |
| Frequency Tolerance | ±100.00ppm |
| Tolerance Condition | @ 25°C |
| Frequency Stability | ±50.00ppm to ±100.00ppm |
| Ageing | ±5ppm max in 1st year |

Electrical Parameters

- | | |
|---|-------------|
| Supply Voltage | 1.8V ±10% |
| Supply Current Typical: | |
| 1.5mA @ 24MHz | |
| 2.0mA @ 32MHz | |
| 3.0mA @ 50MHz | |
| 12.0mA @ 130MHz | |
| Supply Voltage (absolute maximum rating): | -0.5V to 7V |

Operating Temperature Ranges

- 10 to 70°C
- 40 to 85°C
- 55 to 125°C

Output Details


- | | |
|----------------------|---------|
| Output Compatability | CMOS |
| Drive Capability | 15pF |
| Start Up Time: | 5ms max |

Environmental Parameters



- Shock: 10000G, 0.3ms, 1/2 sine
- Vibration: MIL-STD-202G, Method 204D, Condition D: 20G rms, 10Hz-2000Hz swept sine
- Storage Temperature Range: -55 to 125°C




Outline (mm) SM1 = Gold Plated (RoHS)



Pad Connections	Height (H) =
1. NC/EN	SM1 1.09 max
2. GND	SM3 1.21 max
3. Output	SM5 1.21 max
4. +Vs	



Underside View



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Manufacturing Details

- Features:
 - High shock resistance
 - Low acceleration sensitivity
 - Low power consumption
 - Low EMI emission
 - Optional Output Enable/Disable with Tri-State
 - Full military testing available
- Applications:
 - Military & Aerospace -
 - Smart munitions
 - Communications
 - Navigation
 - GPS
 - Industrial, Computer & Communications -
 - Miniature clock oscillator
 - Handheld instrumentation
 - PDA
 - Transponder/Animal migration
 - Medical -
 - Test & Diagnostic equipment
 - Handheld devices
- Solder Process Temperature: 260°C max for 20sec max

Ordering Information

- Frequency*
- Model*
- Termination Variant*
- Output
- Frequency Tolerance (@ 25°C)*
- Frequency Stability*
- Operating Temperature Range*
- Pad 1 Function*
- (*minimum required)
- Termination Variants:
 - SM1 = Gold Plated / SM5 = Solder Dipped
 - (Note: Non-RoHS compliant terminations also available - SM3 = Solder Dipped)
- Example
 - 40.0MHz CXOXHG 1.8V SM1
 - CMOS ±100ppm ±100ppm -40 to 85C NC

Compliance

- | | |
|------------------------------|----------------|
| ■ RoHS Status (2011/65/EU) | Optional |
| ■ REACh Status | Compliant |
| ■ MSL Rating (JDEC-STD-033): | Not Applicable |

Packaging Details

- | | |
|--------------------|--|
| ■ Pack Style: Tray | Supplied on a tray |
| Pack Size: 1 | |
| ■ Pack Style: Reel | Tape & reel in accordance with EIA-481-D |
| Pack Size: 1,000 | |

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Electrical Specification - maximum limiting values 1.8V $\pm$ 10%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
1.0MHz	160.0MHz	-10 to 70	$\pm$ 50.0	-	6	40/60%
		-40 to 85	$\pm$ 100.0	-	6	40/60%
		-55 to 125	$\pm$ 100.0	-	6	40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

Germany: 0800 1808 443

France: 0800 901 383

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com