

### FEATURES

- On-chip reference and track-and-hold**
- On-chip input buffer**
- Power dissipation: 850 mW typical at 105 MSPS**
- 500 MHz analog bandwidth**
- SNR: 67 dB @ 49 MHz AIN at 105 MSPS**
- SFDR: 80 dB @ 49 MHz AIN at 105 MSPS**
- 2.0 V p-p analog input range**
- 5.0 V supply operation**
- 3.3 V CMOS/TTL outputs**
- Twos complement output format**

### APPLICATIONS

- Communications**
- Base stations and zero-IF subsystems**
- Wireless local loop (WLL)**
- Local multipoint distribution service (LMDS)**
- HDTV broadcast cameras and film scanners**

### GENERAL INTRODUCTION

The AD9432 is a 12-bit, monolithic sampling analog-to-digital converter (ADC) with an on-chip track-and-hold circuit and is optimized for high speed conversion and ease of use. The product operates up to a 105 MSPS conversion rate with outstanding dynamic performance over its full operating range.

The ADC requires only a single 5.0 V power supply and a 105 MHz encode clock for full performance operation. No external reference or driver components are required for many applications. The digital outputs are TTL-/CMOS-compatible, and a separate output power supply pin supports interfacing with 3.3 V logic. The encode input supports either differential or single-ended mode and is TTL-/CMOS-compatible.

Fabricated on an advanced BiCMOS process, the AD9432 is available in a 52-lead low profile quad flat package (LQFP) and in a 52-lead thin quad flat package (TQFP\_EP). The AD9432 is specified over the industrial temperature range of  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .

### FUNCTIONAL BLOCK DIAGRAM




Figure 1.

#### Rev. F

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
 Tel: 781.329.4700 [www.analog.com](http://www.analog.com)  
 Fax: 781.461.3113 ©2002–2009 Analog Devices, Inc. All rights reserved.

# AD9432\* PRODUCT PAGE QUICK LINKS

Last Content Update: 02/23/2017

---

## COMPARABLE PARTS

View a parametric search of comparable parts.

## DOCUMENTATION

### Application Notes

- AN-282: Fundamentals of Sampled Data Systems
- AN-345: Grounding for Low-and-High-Frequency Circuits
- AN-501: Aperture Uncertainty and ADC System Performance
- AN-715: A First Approach to IBIS Models: What They Are and How They Are Generated
- AN-737: How ADIsimADC Models an ADC
- AN-756: Sampled Systems and the Effects of Clock Phase Noise and Jitter
- AN-808: Multicarrier CDMA2000 Feasibility
- AN-835: Understanding High Speed ADC Testing and Evaluation
- AN-905: Visual Analog Converter Evaluation Tool Version 1.0 User Manual
- AN-935: Designing an ADC Transformer-Coupled Front End

### Data Sheet

- AD9432: 12-Bit, 80 MSPS/105 MSPS ADC Data Sheet

## TOOLS AND SIMULATIONS

- Visual Analog
- AD9432 IBIS Model

## REFERENCE MATERIALS

### Technical Articles

- Correlating High-Speed ADC Performance to Multicarrier 3G Requirements
- DNL and Some of its Effects on Converter Performance
- MS-2210: Designing Power Supplies for High Speed ADC

## DESIGN RESOURCES

- AD9432 Material Declaration
- PCN-PDN Information
- Quality And Reliability
- Symbols and Footprints

## DISCUSSIONS

View all AD9432 EngineerZone Discussions.

## SAMPLE AND BUY

Visit the product page to see pricing options.

## TECHNICAL SUPPORT

Submit a technical question or find your regional support number.

## DOCUMENT FEEDBACK

Submit feedback for this data sheet.

## TABLE OF CONTENTS

|                                                    |   |                                            |    |
|----------------------------------------------------|---|--------------------------------------------|----|
| Features .....                                     | 1 | Terminology .....                          | 11 |
| Applications .....                                 | 1 | Equivalent Circuits .....                  | 12 |
| General Introduction .....                         | 1 | Theory of Operation .....                  | 13 |
| Functional Block Diagram .....                     | 1 | Analog Input .....                         | 13 |
| Revision History .....                             | 2 | Encode Input .....                         | 13 |
| Specifications .....                               | 3 | Encode Voltage Level Definition .....      | 13 |
| Timing Diagram .....                               | 5 | Digital Outputs .....                      | 14 |
| Absolute Maximum Ratings .....                     | 6 | Voltage Reference .....                    | 14 |
| Explanation of Test Levels .....                   | 6 | Timing .....                               | 14 |
| Thermal Characteristics .....                      | 6 | Applications Information .....             | 15 |
| ESD Caution .....                                  | 6 | Using the AD8138 to Drive the AD9432 ..... | 15 |
| Pin Configurations and Function Descriptions ..... | 7 | Outline Dimensions .....                   | 16 |
| Typical Performance Characteristics .....          | 8 | Ordering Guide .....                       | 16 |

## REVISION HISTORY

### 6/09—Rev. E to Rev. F

|                                                                          |           |
|--------------------------------------------------------------------------|-----------|
| Updated Format .....                                                     | Universal |
| Reorganized Layout .....                                                 | Universal |
| Added TQFP_EP Package .....                                              | Universal |
| Deleted LQFP_ED Package .....                                            | Universal |
| Changes to Thermal Characteristics Section .....                         | 6         |
| Changes to Pin Configurations and Function Descriptions<br>Section ..... | 7         |
| Changes to Terminology Section .....                                     | 11        |
| Deleted Evaluation Board Section .....                                   | 15        |
| Updated Outline Dimensions .....                                         | 16        |
| Changes to Ordering Guide .....                                          | 16        |

### 1/02—Rev. D to Rev. E

|                                                    |    |
|----------------------------------------------------|----|
| Edits to Specifications .....                      | 3  |
| Edits to Absolute Maximum Ratings .....            | 4  |
| Edits to Ordering Guide .....                      | 4  |
| Addition of Text to Using the AD9432 Section ..... | 10 |
| Edits to Figure 17a .....                          | 15 |
| Edits to Figure 17b .....                          | 16 |
| Addition of SQ-52 Package Outline .....            | 18 |

## SPECIFICATIONS

$V_{DD} = 3.3\text{ V}$ ,  $V_{CC} = 5.0\text{ V}$ ; external reference; differential encode input, unless otherwise noted.

Table 1.

| Parameter                                                                         | Temp | Test Level | 80 MSPS         |       |       | 105 MSPS        |       |       | Unit   |
|-----------------------------------------------------------------------------------|------|------------|-----------------|-------|-------|-----------------|-------|-------|--------|
| Resolution                                                                        |      |            | Min             | Typ   | Max   | Min             | Typ   | Max   | Bits   |
| DC ACCURACY                                                                       |      |            |                 |       |       |                 |       |       |        |
| Differential Nonlinearity (DNL)                                                   | 25°C | I          | −0.75           | ±0.25 | +0.75 | −0.75           | ±0.25 | +0.75 | LSB    |
|                                                                                   | Full | VI         | −1.0            | ±0.5  | +1.0  | −1.0            | ±0.5  | +1.0  | LSB    |
| Integral Nonlinearity (INL)                                                       | 25°C | I          | −1.0            | ±0.5  | +1.0  | −1.0            | ±0.5  | +1.0  | LSB    |
|                                                                                   | Full | VI         | −1.5            | ±1.0  | +1.5  | −1.5            | ±1.0  | +1.5  | LSB    |
| No Missing Codes                                                                  | Full | VI         | Guaranteed      |       |       | Guaranteed      |       |       |        |
| Gain Error <sup>1</sup>                                                           | 25°C | I          | −5              | +2    | +7    | −5              | +2    | +7    | % FS   |
| Gain Tempco <sup>1</sup>                                                          | Full | V          |                 | 150   |       |                 | 150   |       | ppm/°C |
| ANALOG INPUTS (AIN, AIN)                                                          |      |            |                 |       |       |                 |       |       |        |
| Input Voltage Range                                                               | Full | V          |                 | 2     |       |                 | 2     |       | V p-p  |
| Common-Mode Voltage                                                               | Full | V          |                 | 3.0   |       |                 | 3.0   |       | V      |
| Input Offset Voltage                                                              | Full | VI         | −5              | ±0    | +5    | −5              | ±0    | +5    | mV     |
| Input Resistance                                                                  | Full | VI         | 2               | 3     | 4     | 2               | 3     | 4     | kΩ     |
| Input Capacitance                                                                 | 25°C | V          |                 | 4     |       |                 | 4     |       | pF     |
| Analog Bandwidth, Full Power                                                      | 25°C | V          |                 | 500   |       |                 | 500   |       | MHz    |
| ANALOG REFERENCE                                                                  |      |            |                 |       |       |                 |       |       |        |
| Output Voltage                                                                    | Full | VI         | 2.4             | 2.5   | 2.6   | 2.4             | 2.5   | 2.6   | V      |
| Tempco                                                                            | Full | V          |                 | 50    |       |                 | 50    |       | ppm/°C |
| Input Bias Current                                                                | Full | VI         |                 | 15    | 50    |                 | 15    | 50    | μA     |
| SWITCHING PERFORMANCE                                                             |      |            |                 |       |       |                 |       |       |        |
| Maximum Conversion Rate                                                           | Full | VI         | 80              |       |       | 105             |       |       | MSPS   |
| Minimum Conversion Rate                                                           | Full | IV         |                 |       | 1     |                 |       | 1     | MSPS   |
| Encode Pulse Width High ( $t_{EH}$ )                                              | 25°C | IV         | 4.0             | 6.2   |       | 4.0             | 4.8   |       | ns     |
| Encode Pulse Width Low ( $t_{EL}$ )                                               | 25°C | IV         | 4.0             | 6.2   |       | 4.0             | 4.8   |       | ns     |
| Aperture Delay ( $t_A$ )                                                          | 25°C | V          |                 | 2.0   |       |                 | 2.0   |       | ns     |
| Aperture Uncertainty (Jitter)                                                     | 25°C | V          |                 | 0.25  |       |                 | 0.25  |       | ps rms |
| Output Valid Time ( $t_V$ ) <sup>2</sup>                                          | Full | VI         | 3.0             | 5.3   |       | 3.0             | 5.3   |       | ns     |
| Output Propagation Delay ( $t_{PD}$ ) <sup>2</sup>                                | Full | VI         |                 | 5.5   | 8.0   |                 | 5.5   | 8.0   | ns     |
| Output Rise Time ( $t_R$ ) <sup>2</sup>                                           | Full | V          |                 | 2.1   |       |                 | 2.1   |       | ns     |
| Output Fall Time ( $t_F$ ) <sup>2</sup>                                           | Full | V          |                 | 1.9   |       |                 | 1.9   |       | ns     |
| Out-of-Range Recovery Time                                                        | 25°C | V          |                 | 2     |       |                 | 2     |       | ns     |
| Transient Response Time                                                           | 25°C | V          |                 | 2     |       |                 | 2     |       | ns     |
| Latency                                                                           | Full | IV         |                 | 10    |       |                 | 10    |       | Cycles |
| DIGITAL INPUTS                                                                    |      |            |                 |       |       |                 |       |       |        |
| Encode Input Common Mode                                                          | Full | V          |                 | 1.6   |       |                 | 1.6   |       | V      |
| Differential Input<br>( $\overline{\text{ENCODE}}$ , $\overline{\text{ENCODE}}$ ) | Full | V          |                 | 750   |       |                 | 750   |       | mV     |
| Single-Ended Input                                                                |      |            |                 |       |       |                 |       |       |        |
| Logic 1 Voltage                                                                   | Full | IV         | 2.0             |       |       | 2.0             |       |       | V      |
| Logic 0 Voltage                                                                   | Full | IV         |                 |       | 0.8   |                 |       | 0.8   | V      |
| Input Resistance                                                                  | Full | VI         | 3               | 5     | 8     | 3               | 5     | 8     | kΩ     |
| Input Capacitance                                                                 | 25°C | V          |                 | 4.5   |       |                 | 4.5   |       | pF     |
| DIGITAL OUTPUTS                                                                   |      |            |                 |       |       |                 |       |       |        |
| Logic 1 Voltage ( $V_{DD} = 3.3\text{ V}$ )                                       | Full | VI         | $V_{DD} - 0.05$ |       |       | $V_{DD} - 0.05$ |       |       | V      |
| Logic 0 Voltage ( $V_{DD} = 3.3\text{ V}$ )                                       | Full | VI         |                 | 0.05  |       |                 | 0.05  |       | V      |
| Output Coding                                                                     |      |            | Twos complement |       |       | Twos complement |       |       |        |

| Parameter                                                                              | Temp | Test Level | 80 MSPS |      |      | 105 MSPS |      |      | Unit |
|----------------------------------------------------------------------------------------|------|------------|---------|------|------|----------|------|------|------|
|                                                                                        |      |            | Min     | Typ  | Max  | Min      | Typ  | Max  |      |
| <b>POWER SUPPLY</b>                                                                    |      |            |         |      |      |          |      |      |      |
| Power Dissipation <sup>3</sup>                                                         | Full | VI         |         | 790  | 1000 |          | 850  | 1100 | mW   |
| I <sub>VCC</sub>                                                                       | Full | VI         |         | 158  | 200  |          | 170  | 220  | mA   |
| I <sub>VDD</sub>                                                                       | Full | VI         |         | 9.5  | 12.2 |          | 12.5 | 16   | mA   |
| Power Supply Rejection Ratio (PSRR)                                                    | 25°C | I          | −5      | +0.5 | +5   | −5       | +0.5 | +5   | mV/V |
| <b>DYNAMIC PERFORMANCE<sup>4</sup></b>                                                 |      |            |         |      |      |          |      |      |      |
| <b>Signal-to-Noise Ratio (SNR) (Without Harmonics)</b>                                 |      |            |         |      |      |          |      |      |      |
| f <sub>IN</sub> = 10 MHz                                                               | 25°C | I          | 65.5    | 67.5 |      | 65.5     | 67.5 |      | dB   |
| f <sub>IN</sub> = 40 MHz                                                               | 25°C | I          | 65      | 67.2 |      |          | 67.2 |      | dB   |
| f <sub>IN</sub> = 49 MHz                                                               | 25°C | I          |         | 67.0 |      | 64       | 67.0 |      | dB   |
| f <sub>IN</sub> = 70 MHz                                                               | 25°C | V          |         | 66.1 |      |          | 66.1 |      | dB   |
| <b>Signal-to-Noise and Distortion (SINAD) Ratio (with Harmonics)</b>                   |      |            |         |      |      |          |      |      |      |
| f <sub>IN</sub> = 10 MHz                                                               | 25°C | I          | 65      | 67.2 |      | 65       | 67.2 |      | dB   |
| f <sub>IN</sub> = 40 MHz                                                               | 25°C | I          | 64.5    | 66.9 |      |          | 66.9 |      | dB   |
| f <sub>IN</sub> = 49 MHz                                                               | 25°C | I          |         | 66.7 |      | 63       | 66.7 |      | dB   |
| f <sub>IN</sub> = 70 MHz                                                               | 25°C | V          |         | 65.8 |      |          | 65.8 |      | dB   |
| <b>Effective Number of Bits (ENOB)</b>                                                 |      |            |         |      |      |          |      |      |      |
| f <sub>IN</sub> = 10 MHz                                                               | 25°C | V          |         | 11.0 |      |          | 11.0 |      | Bits |
| f <sub>IN</sub> = 40 MHz                                                               | 25°C | V          |         | 10.9 |      |          | 10.9 |      | Bits |
| f <sub>IN</sub> = 49 MHz                                                               | 25°C | V          |         | 10.9 |      |          | 10.9 |      | Bits |
| f <sub>IN</sub> = 70 MHz                                                               | 25°C | V          |         | 10.7 |      |          | 10.7 |      | Bits |
| <b>Second-Order and Third-Order Harmonic Distortion</b>                                |      |            |         |      |      |          |      |      |      |
| f <sub>IN</sub> = 10 MHz                                                               | 25°C | I          | −75     | −85  |      | −75      | −85  |      | dBc  |
| f <sub>IN</sub> = 40 MHz                                                               | 25°C | I          | −73     | −85  |      |          | −83  |      | dBc  |
| f <sub>IN</sub> = 49 MHz                                                               | 25°C | I          |         | −83  |      | −72      | −80  |      | dBc  |
| f <sub>IN</sub> = 70 MHz                                                               | 25°C | V          |         | −80  |      |          | −78  |      | dBc  |
| <b>Worst Other Harmonic or Spur (Excluding Second-Order and Third-Order Harmonics)</b> |      |            |         |      |      |          |      |      |      |
| f <sub>IN</sub> = 10 MHz                                                               | 25°C | I          | −80     | −90  |      | −80      | −90  |      | dBc  |
| f <sub>IN</sub> = 40 MHz                                                               | 25°C | I          | −80     | −90  |      |          | −90  |      | dBc  |
| f <sub>IN</sub> = 49 MHz                                                               | 25°C | I          |         | −90  |      | −80      | −90  |      | dBc  |
| f <sub>IN</sub> = 70 MHz                                                               | 25°C | V          |         | −90  |      |          | −90  |      | dBc  |
| <b>Two-Tone Intermodulation Distortion (IMD)</b>                                       |      |            |         |      |      |          |      |      |      |
| f <sub>IN1</sub> = 29.3 MHz; f <sub>IN2</sub> = 30.3 MHz                               | 25°C | V          |         | −75  |      |          | −75  |      | dBc  |
| f <sub>IN1</sub> = 70.3 MHz; f <sub>IN2</sub> = 71.3 MHz                               | 25°C | V          |         | −66  |      |          | −66  |      | dBc  |

<sup>1</sup> Gain error and gain temperature coefficients are based on the ADC only (with a fixed 2.5 V external reference and a 2 V p-p differential analog input).

<sup>2</sup> t<sub>V</sub> and t<sub>PD</sub> are measured from the transition points of the ENCODE input to the 50%/50% levels of the digital output swing. The digital output load during testing is not to exceed an ac load of 10 pF or a dc current of ±40 µA. Rise and fall times are measured from 10% to 90%.

<sup>3</sup> Power dissipation measured with encode at rated speed and a dc analog input (outputs static, I<sub>VDD</sub> = 0).

<sup>4</sup> SNR/harmonics based on an analog input voltage of −0.5 dBFS referenced to a 2 V full-scale input range.

TIMING DIAGRAM




Figure 2. Timing Diagram

00587-003

## ABSOLUTE MAXIMUM RATINGS

Table 2.

| Parameter                    | Rating                     |
|------------------------------|----------------------------|
| $V_{DD}$                     | 6 V                        |
| $V_{CC}$                     | 6 V                        |
| Analog Inputs                | −0.5 V to $V_{CC} + 0.5$ V |
| Digital Inputs               | −0.5 V to $V_{DD} + 0.5$ V |
| VREFIN                       | −0.5 V to $V_{CC} + 0.5$ V |
| Digital Output Current       | 20 mA                      |
| Operating Temperature Range  | −55°C to +125°C            |
| Storage Temperature Range    | −65°C to +150°C            |
| Maximum Junction Temperature | 150°C                      |
| Maximum Case Temperature     | 150°C                      |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### EXPLANATION OF TEST LEVELS

- I 100% production tested.
- II 100% production tested at 25°C and sample tested at specified temperatures.
- III Sample tested only.
- IV Parameter is guaranteed by design and characterization testing.
- V Parameter is a typical value only.
- VI 100% production tested at 25°C; guaranteed by design and characterization testing for industrial temperature range.

## THERMAL CHARACTERISTICS

Table 3 lists AD9432 thermal characteristics for simulated typical performance in a 4-layer JEDEC board, horizontal orientation.

Table 3. Thermal Resistance

| Package Type                           | $\theta_{JA}$ | $\theta_{JMA}$ | $\theta_{JC}$ | Unit |
|----------------------------------------|---------------|----------------|---------------|------|
| 52-Lead LQFP (ST-52)                   |               |                |               |      |
| No Airflow                             | 50            |                |               | °C/W |
| 52-Lead TQFP_EP (SV-52-2) <sup>1</sup> |               |                | 2             | °C/W |
| No Airflow                             | 19.3          |                |               | °C/W |
| 1.0 m/s Airflow                        |               | 16             |               | °C/W |


<sup>1</sup> Bottom of package (soldered exposed pad).

## ESD CAUTION




**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

## PIN CONFIGURATIONS AND FUNCTION DESCRIPTIONS



NOTES  
1. DNC = DO NOT CONNECT.

00587-002



NOTES  
1. ALTHOUGH NOT REQUIRED IN ALL APPLICATIONS, THE EXPOSED PADDLE ON THE UNDERSIDE OF THE PACKAGE SHOULD BE SOLDERED TO THE GROUND PLANE. SOLDERING THE EXPOSED PADDLE TO THE PCB INCREASES THE RELIABILITY OF THE SOLDER JOINTS, MAXIMIZING THE THERMAL CAPABILITY OF THE PACKAGE.

00587-044







Figure 3. Pin Configuration, LQFP







Figure 4. Pin Configuration, TQFP\_EP

Table 4. Pin Function Descriptions

| Pin No.                                            | Mnemonic              | Description                                                                                                                                                                                                                                                                             |
|----------------------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1, 3, 4, 9, 11, 33, 34, 35, 38, 39, 40, 43, 48, 51 | GND                   | Analog Ground.                                                                                                                                                                                                                                                                          |
| 2, 5, 6, 10, 36, 37, 42, 44, 47, 52                | V <sub>CC</sub>       | Analog Supply (5 V).                                                                                                                                                                                                                                                                    |
| 7                                                  | ENCODE                | Encode Clock for ADC, Complementary.                                                                                                                                                                                                                                                    |
| 8                                                  | ENCODE                | Encode Clock for ADC, True. ADC samples on rising edge of ENCODE.                                                                                                                                                                                                                       |
| 12, 21, 24, 31                                     | DGND                  | Digital Output Ground.                                                                                                                                                                                                                                                                  |
| 13, 22, 23, 32                                     | V <sub>DD</sub>       | Digital Output Power Supply (2.7 V to 3.6 V).                                                                                                                                                                                                                                           |
| 14                                                 | OR                    | Out-of-Range Output.                                                                                                                                                                                                                                                                    |
| 15 to 20, 25 to 30                                 | D11 to D6, D5 to D0   | Digital Output.                                                                                                                                                                                                                                                                         |
| 41                                                 | DNC                   | Do Not Connect.                                                                                                                                                                                                                                                                         |
| 45                                                 | VREFIN                | Reference Input for ADC (2.5 V Typical). Bypass with 0.1 $\mu$ F capacitor to ground.                                                                                                                                                                                                   |
| 46                                                 | VREFOUT               | Internal Reference Output (2.5 V Typical).                                                                                                                                                                                                                                              |
| 49                                                 | AIN                   | Analog Input, True.                                                                                                                                                                                                                                                                     |
| 50                                                 | AIN                   | Analog Input, Complementary.                                                                                                                                                                                                                                                            |
|                                                    | Exposed Pad (TQFP_EP) | Although not required in all applications, the exposed paddle on the underside of the TQFP_EP package should be soldered to the ground plane. Soldering the exposed paddle to the PCB increases the reliability of the solder joints, maximizing the thermal capability of the package. |

## TYPICAL PERFORMANCE CHARACTERISTICS

Figure 5. SNR/SINAD/SFDR vs.  $f_{IN}$ ,  $f_{IN} = 10.3$  MHzFigure 8. SNR vs.  $f_{IN}$ , Encode = 105 MSPSFigure 6. Second-Order and Third-Order Harmonics vs.  $f_{IN}$ ,  $f_{IN} = 10.3$  MHzFigure 9. Second-Order and Third-Order Harmonics vs.  $f_{IN}$ ,  $f_{IN} = 105$  MSPSFigure 7. SINAD vs.  $f_{IN}$ ,  $f_{IN} = 105$  MSPSFigure 10. Worst Other (Excluding Second-Order and Third-Order Harmonics) vs.  $f_{IN}$ ,  $f_{IN} = 105$  MSPS

Figure 11. FFT:  $f_s = 105$  MSPS,  $f_{IN} = 10.3$  MHzFigure 14. FFT:  $f_s = 105$  MSPS,  $f_{IN} = 50.3$  MHzFigure 12. FFT:  $f_s = 105$  MSPS,  $f_{IN} = 27$  MHzFigure 15. Two-Tone FFT, Wideband:  $f_s = 105$  MSPS, AIN1 = 29.3 MHz, AIN2 = 30.3 MHzFigure 13. FFT:  $f_s = 105$  MSPS,  $f_{IN} = 40.9$  MHzFigure 16. Two-Tone FFT, Wideband:  $f_s = 105$  MSPS, AIN1 = 70.3 MHz, AIN2 = 71.3 MHz




Figure 17. Single-Tone SFDR,  $f_s = 105$  MSPS,  $f_{IN} = 50.3$  MHz




Figure 19. Integral Nonlinearity,  $f_s = 105$  MSPS




Figure 18. Differential Nonlinearity,  $f_s = 105$  MSPS




Figure 20. Voltage Reference Output vs. Current Load

## TERMINOLOGY

### Analog Bandwidth

The analog input frequency at which the spectral power of the fundamental frequency (as determined by the FFT analysis) is reduced by 3 dB.

### Aperture Delay

The delay between a differential crossing of ENCODE and ENCODE and the instant at which the analog input is sampled.

### Aperture Uncertainty (Jitter)

The sample-to-sample variation in aperture delay.

### Differential Nonlinearity (DNL)

The deviation of any code from an ideal 1 LSB step.

### Effective Number of Bits (ENOB)

The effective number of bits (ENOB) is calculated from the measured SNR based on the following equation:

$$ENOB = \frac{SNR_{MEASURED} - 1.76 \text{ dB} + 20 \log \left( \frac{\text{Full-Scale Amplitude}}{\text{Input Amplitude}} \right)}{6.02}$$

### Encode Pulse Width/Duty Cycle

Pulse width high is the minimum amount of time that the encode pulse should be left in the Logic 1 state to achieve the rated performance. Pulse width low is the minimum amount of time that the encode pulse should be left in the Logic 0 state. At a given clock rate, these specifications define an acceptable encode duty cycle.

### Harmonic Distortion

The ratio of the rms signal amplitude fundamental frequency to the rms signal amplitude of a single harmonic component (second, third, and so on); reported in dBc.

### Integral Nonlinearity (INL)

The deviation of the transfer function from a reference line measured in fractions of 1 LSB using a “best straight line” determined by a least square curve fit.

### Maximum Conversion Rate

The maximum encode rate at which parametric testing is performed.

### Minimum Conversion Rate

The encode rate at which the SNR of the lowest analog signal frequency drops by no more than 3 dB below the guaranteed limit.

### Output Propagation Delay

The delay between a differential crossing of ENCODE and ENCODE and the time when all output data bits are within valid logic levels.

### Power Supply Rejection Ratio (PSRR)

The ratio of a change in input offset voltage to a change in power supply voltage.

### Signal-to-Noise and Distortion (SINAD) Ratio

The ratio of the rms signal amplitude (set at 1 dB below full scale) to the rms value of the sum of all other spectral components, including harmonics but excluding dc.

### Signal-to-Noise Ratio (SNR)

The ratio of the rms signal amplitude (set at 1 dB below full scale) to the rms value of the sum of all other spectral components, excluding the first five harmonics and dc.

### Spurious-Free Dynamic Range (SFDR)

The ratio of the rms signal amplitude to the rms value of the peak spurious spectral component. The peak spurious component may or may not be a harmonic. May be reported in dBc (degrades as signal level is lowered) or in dBFS (always related back to converter full scale).

### Two-Tone Intermodulation Distortion Rejection

The ratio of the rms value of either input tone ( $f_1$ ,  $f_2$ ) to the rms value of the worst third-order intermodulation product; reported in dBc. Products are located at  $2f_1 - f_2$  and  $2f_2 - f_1$ .

### Two-Tone SFDR

The ratio of the rms value of either input tone ( $f_1$ ,  $f_2$ ) to the rms value of the peak spurious component. The peak spurious component may or may not be an IMD product. May be reported in dBc (degrades as signal level is lowered) or in dBFS (always related back to converter full scale).

### Worst Other Spur

The ratio of the rms signal amplitude to the rms value of the worst spurious component (excluding the second-order and third-order harmonic); reported in dBc.

## EQUIVALENT CIRCUITS




Figure 21. Voltage Reference Input Circuit




Figure 24. Digital Output Circuit




Figure 22. Voltage Reference Output Circuit




Figure 25. Analog Input Circuit




Figure 23. Encode Input Circuit

## THEORY OF OPERATION

The AD9432 is a 12-bit pipeline converter that uses a switched-capacitor architecture. Optimized for high speed, this converter provides flat dynamic performance up to frequencies near Nyquist. DNL transitional errors are calibrated at final test to a typical accuracy of 0.25 LSB or less.

### ANALOG INPUT

The analog input to the AD9432 is a differential buffer. The input buffer is self-biased by an on-chip resistor divider that sets the dc common-mode voltage to a nominal 3 V (see the Equivalent Circuits section). Rated performance is achieved by driving the input differentially. The minimum input offset voltage is obtained when driving from a source with a low differential source impedance, such as a transformer in ac applications. Capacitive coupling at the inputs increases the input offset voltage by as much as  $\pm 25$  mV. Driving the ADC single-ended degrades performance. For best dynamic performance, impedances at  $A_{IN}$  and  $\overline{A_{IN}}$  should match.

Special care was taken in the design of the analog input section of the AD9432 to prevent damage and corruption of data when the input is overdriven. The nominal input range is 2 V p-p. Each analog input is 1 V p-p when driven differentially.




Figure 26. Full-Scale Analog Input Range

### ENCODE INPUT

Any high speed ADC is extremely sensitive to the quality of the sampling clock provided by the user. A track-and-hold circuit is essentially a mixer, and any noise, distortion, or timing jitter on the clock is combined with the desired signal at the ADC output. For this reason, considerable care has been taken in the design of the encode input of the AD9432, and the user is advised to give commensurate thought to the clock source. The encode input supports differential or single-ended mode and is fully TTL-/CMOS-compatible.

Note that the encode inputs cannot be driven directly from PECL level signals ( $V_{IHD}$  is 3.5 V maximum). PECL level signals can easily be accommodated by ac coupling, as shown in Figure 27. Good performance is obtained using an MC10EL16 translator in the circuit to drive the encode inputs.




Figure 27. AC Coupling to Encode Inputs

### ENCODE VOLTAGE LEVEL DEFINITION

The voltage level definitions for driving ENCODE and  $\overline{ENCODE}$  in single-ended and differential mode are shown in Figure 28.




Figure 28. Differential and Single-Ended Input Levels

Table 5. Encode Inputs

| Input                                         | Min    | Nominal | Max   |
|-----------------------------------------------|--------|---------|-------|
| Differential Signal Amplitude ( $V_{ID}$ )    | 500 mV | 750 mV  |       |
| High Differential Input Voltage ( $V_{IHD}$ ) |        |         | 3.5 V |
| Low Differential Input Voltage ( $V_{ILD}$ )  | 0 V    |         |       |
| Common-Mode Input ( $V_{ICM}$ )               | 1.25 V | 1.6 V   |       |
| High Single-Ended Voltage ( $V_{IHS}$ )       | 2 V    |         | 3.5 V |
| Low Single-Ended Voltage ( $V_{ILS}$ )        | 0 V    |         | 0.8 V |

Often, the cleanest clock source is a crystal oscillator producing a pure sine wave. In this configuration, or with any roughly symmetrical clock input, the input can be ac-coupled and biased to a reference voltage that also provides the encode. This ensures that the reference voltage is centered on the encode signal.

## DIGITAL OUTPUTS

The digital outputs are 3.3 V (2.7 V to 3.6 V) TTL-/CMOS-compatible for lower power consumption. The output data format is twos complement (see Table 6).

**Table 6. Twos Complement Output Coding ( $V_{REF} = 2.5$  V)**

| Code  | AIN – AIN (V) | Digital Output |
|-------|---------------|----------------|
| +2047 | 1.000         | 0111 1111 1111 |
| ...   | ...           | ...            |
| 0     | 0             | 0000 0000 0000 |
| –1    | –0.00049      | 1111 1111 1111 |
| ...   | ...           | ...            |
| –2048 | –1.000        | 1000 0000 0000 |

The out-of-range (OR) output is logic low for normal operation. During any clock cycle when the ADC output data (Dx) reaches positive or negative full scale (+2047 or –2048), the OR output goes high. The OR output is internally generated each clock cycle. It has the same pipeline latency and propagation delay as the ADC output data and remains high until the output data reflects an in-range condition. The ADC output bits (Dx) do not roll over and, therefore, remain at positive or negative full scale (+2047 or –2048) while the OR output is high.

## VOLTAGE REFERENCE

A stable and accurate 2.5 V voltage reference is built into the AD9432 (VREFOUT). In normal operation, the internal reference is used by strapping Pin 45 to Pin 46 and placing a 0.1  $\mu$ F decoupling capacitor at VREFIN.

The input range can be adjusted by varying the reference voltage applied to the AD9432. No appreciable degradation in performance occurs when the reference is adjusted  $\pm 5\%$ . The full-scale range of the ADC tracks reference voltage changes linearly.

## TIMING

The AD9432 provides latched data outputs, with 10 pipeline delays. Data outputs are included or available one propagation delay ( $t_{PD}$ ) after the rising edge of the encode command (see Figure 2). The length of the output data lines and the loads placed on them should be minimized to reduce transients within the AD9432; these transients can detract from the dynamic performance of the converter.

The minimum guaranteed conversion rate of the AD9432 is 1 MSPS. At internal clock rates below 1 MSPS, dynamic performance may degrade. Therefore, input clock rates below 1 MHz should be avoided.

During initial power-up, or whenever the clock to the AD9432 is interrupted, the output data will not be accurate for 200 ns or 10 clock cycles, whichever is longer.

## APPLICATIONS INFORMATION

### USING THE AD8138 TO DRIVE THE AD9432

The AD8138 differential output op amp can be used to drive the AD9432 in dc-coupled applications. The AD8138 was specifically designed for ADC driver applications. Superior SNR performance is maintained up to analog frequencies of 30 MHz. The AD8138 op amp provides single-ended-to-differential conversion, which allows for a low cost alternative to transformer coupling for ac applications, as well.

The circuit in Figure 29 was breadboarded, and the measured performance is shown in Figure 30 and Figure 31. These figures are for  $\pm 5$  V supplies at the AD8138; with a single 5 V supply at the AD8138, performance dropped by about 1 dB to 2 dB.

Figure 30 shows SNR and SINAD for a  $-1$  dBFS analog input frequency varied from 2 MHz to 40 MHz with an encode rate of 105 MSPS. The measurements are for nominal conditions at room temperature. Figure 31 shows the second-order and third-order harmonic distortion performance under the same conditions.

The dc common-mode voltage for the AD8138 outputs can be adjusted via the  $V_{OCM}$  input to provide the 3 V common-mode voltage that the AD9432 inputs require.




Figure 29. AD8138/AD9432 Schematic




Figure 30. Measured SNR and SINAD (Encode = 105 MSPS)





Figure 31. Measured Second-Order and Third-Order Harmonic Distortion (Encode = 105 MSPS)

## OUTLINE DIMENSIONS




COMPLIANT TO JEDEC STANDARDS MS-026-BCC

Figure 32. 52-Lead Low Profile Quad Flat Package [LQFP]  
(ST-52)

Dimensions shown in millimeters

051708-A



COMPLIANT TO JEDEC STANDARDS MS-026-ACC

Figure 33. 52-Lead Thin Quad Flat Package, Exposed Pad [TQFP\_EP]  
(SV-52-2)

Dimensions shown in millimeters

072508-A

## ORDERING GUIDE

| Model                       | Temperature Range | Package Description                                   | Package Option |
|-----------------------------|-------------------|-------------------------------------------------------|----------------|
| AD9432BSTZ-80 <sup>1</sup>  | −40°C to +85°C    | 52-Lead Low Profile Quad Flat Package [LQFP]          | ST-52          |
| AD9432BSTZ-105 <sup>1</sup> | −40°C to +85°C    | 52-Lead Low Profile Quad Flat Package [LQFP]          | ST-52          |
| AD9432BSVZ-80 <sup>1</sup>  | −40°C to +85°C    | 52-Lead Thin Quad Flat Package, Exposed Pad [TQFP_EP] | SV-52-2        |
| AD9432BSVZ-105 <sup>1</sup> | −40°C to +85°C    | 52-Lead Thin Quad Flat Package, Exposed Pad [TQFP_EP] | SV-52-2        |

<sup>1</sup> Z = RoHS Compliant Part.