

isc N-Channel MOSFET Transistor


2SK1199

DESCRIPTION

- Drain Current $-I_D = 2A @ T_C = 25^\circ C$
- Drain Source Voltage-
: $V_{DSS} = 900V(\text{Min})$
- Fast Switching Speed


APPLICATIONS

- Designed for high voltage, high speed power switching applications such as switching regulators, converters, solenoid and relay drivers.



ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ C$)

SYMBOL	ARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage ($V_{GS}=0$)	900	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-continuous@ $TC=25^\circ C$	2	A
P_{tot}	Total Dissipation@ $TC=25^\circ C$	50	W
T_j	Max. Operating Junction Temperature	150	$^\circ C$
T_{stg}	Storage Temperature Range	-55~150	$^\circ C$



DIM	mm	
	MIN	MAX
A	15.70	15.90
B	9.90	10.10
C	4.20	4.40
D	0.70	0.90
F	3.40	3.60
G	4.98	5.18
H	2.70	2.90
J	0.44	0.46
K	13.20	13.40
L	1.10	1.30
Q	2.70	2.90
R	2.50	2.70
S	1.29	1.31
U	6.45	6.65
V	8.66	8.86

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th j-c}$	Thermal Resistance, Junction to Case	0.83	$^\circ C/W$
$R_{th j-a}$	Thermal Resistance, Junction to Ambient	35	$^\circ C/W$

isc N-Channel Mosfet Transistor

2SK1199

• ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0; I_D=10\text{mA}$	900			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=10 V_{GS}; I_D=1\text{mA}$	2.0		4.0	V
$R_{DS(on)}$	Drain-Source On-stage Resistance	$V_{GS}=10\text{V}; I_D=5\text{A}$		5.0	7.0	Ω
I_{GSS}	Gate Source Leakage Current	$V_{GS}= \pm 16\text{V}; V_{DS}=0$			± 10	μA
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=720\text{V}; V_{GS}=0$			250	μA
V_{SD}	Diode Forward Voltage	$I_F=2\text{A}; V_{GS}=0$		0.9		V
t_r	Rise time	$V_{GS}=10\text{V}; I_D=1\text{A};$ $R_L=30\ \Omega$		60		ns
t_{on}	Turn-on time			70		ns
t_f	Fall time			60		ns
t_{off}	Turn-off time			125		ns