

PASTERVACK

SMB Plug Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

TECHNICAL DATA SHEET

PE4366

Configuration	
Connector	SMB Plug
Connector Interface Type	Thru Hole
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight
Electrical Specifications	
Impedance, Ohms	50
Mechanical Specifications	
Size	
Length, in [mm]	0.467 [11.86]
Width/Dia., in [mm]	0.25 [6.35]
Height, in [mm]	0.25 [6.35]
Weight, lbs [g]	0.055 [24.95]
Connector	
Туре	SMB Plug
Contact Material and Plating	Gold
Body Material and Plating	Brass, Gold
Dielectric Type	PTFE
Compliance Certifications (visit www.Pasternack.c	com for current document)
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
SMB Plug Connector Solder Attachment Thru Hole PC	B, .200 inch x .067 inch Hole Spacing from Pasternack Enterprises
	orders. Our RF, microwave and fiber optic products maintain a 99%
availability and are part of the broadest selection in the	industry.

inventory and certifications: SMB Plug Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing PE4366

URL: http://www.pasternack.com/smb-plug-standard-thru-hole-pcb-connector-pe4366-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com PE4366 CAD Drawing

SMB Plug Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

