

isc N-Channel MOSFET Transistor IRFR13N20D, IIRFR13N20D

• FEATURES

- Static drain-source on-resistance:
 $R_{DS(on)} \leq 235m\Omega$
- Enhancement mode:
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

• DESCRIPTION



- High frequency DC-DC converters

• ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{DSS}	Drain-Source Voltage	200	V
V _{GS}	Gate-Source Voltage	±30	V
I _D	Drain Current-Continuous	13	A
I _{DM}	Drain Current-Single Pulsed	52	A
P _D	Total Dissipation @T _c =25°C	110	W
T _j	Max. Operating Junction Temperature	175	°C
T _{stg}	Storage Temperature	-55~175	°C

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th(j-c)}	Channel-to-case thermal resistance	1.4	°C/W
R _{th(j-a)}	Channel-to-ambient thermal resistance	110	°C/W



DIM	mm	
	MIN	MAX
A	6.40	6.60
B	5.20	5.40
C	1.15	1.35
D	5.70	6.10
F	0.65	
G	0.75	
H	2.10	2.50
J	2.10	2.40
K	0.40	0.60
L	0.90	1.10
Q	9.90	10.1

isc N-Channel MOSFET Transistor IRFR13N20D, IIRFR13N20D

ELECTRICAL CHARACTERISTICS

$T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V; I_D=250\ \mu\text{A}$	200			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}; I_D=250\ \mu\text{A}$	3		5.5	V
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V; I_D=8A$			235	$\text{m}\Omega$
I_{GSS}	Gate-Source Leakage Current	$V_{GS} = \pm 30V$			± 0.1	μA
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=200V; V_{GS}=0V$			25	μA
V_{SD}	Diode forward voltage	$I_s=7.8A, V_{GS}=0V$			1.3	V