



4 Section Bandpass Filter With SMA Female Connectors Operating From 869 MHz To 894 MHz With a 25 MHz Passband

TECHNICAL DATA SHEET

PE8706

4 Section Bandpass Filter With SMA Female Connectors Operating From 869 MHz To 894 MHz With a 25 MHz Passband

Configuration

Design	Combline Filter
Connector 1	SMA Female
Connector 2	SMA Female
Passband Frequency Range, MHz	869 to 894

Electrical Specifications

ourour opcomodución	
Passband Minimum Frequency, MHz	869
Passband Maximum Frequency, MHz	894
Impedance, Ohms	50
Maximum Insertion Loss, dB	1.5
Passband Maximum VSWR	1.5:1
Maximum Input Power, Watts	5
Rejection at 781.5 MHz	50 dB
Rejection at 981.5 MHz	50 dB

Mechanical Specifications

Connector 1

Type SMA Female

Connector 2

Type SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/4-section-band-pass-filter-869-mhz-894-mhz-passband-25-mhz-pe8706-p.aspx

4 Section Bandpass Filter With SMA Female Connectors Operating From 869 MHz To 894 MHz With a 25 MHz Passband from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE8706 CAD Drawing

4 Section Bandpass Filter With SMA Female Connectors Operating From 869 MHz To 894 MHz With a 25 MHz Passband

