

Insert label - EMT (35X28)R - 0801602

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insert label, Roll, white, unlabeled, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped into marker carrier, lettering field size: 35 x 28 mm

Why buy this product

- EMT ... insert labels for labeling various marking collars
- Thanks to their special shape, EMT ... insert labels remain securely inside the collar once inserted
- Quick and inexpensive marking with THERMOMARK ... roll printers from PHOENIX CONTACT
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences. The marking is even suitable for use under harsh industrial conditions.
- Marking service: Phoenix Contact can custom-mark all EMT ... markers according to your requirements

Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 1 STK |
| GTIN | |
| GTIN | 4046356673075 |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 28 mm |
| Width (a) | 35 mm |

Ambient conditions

| | |
|---------------------------------|--------------------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Recommended storage conditions | 23 °C / 50 % relative humidity |

General

| | |
|----------------|--------------------------------|
| Color | white |
| Components | free from silicone and halogen |
| Material | Polyester |
| RoHS compliant | Yes |

Insert label - EMT (35X28)R - 0801602

Technical data

General

| | |
|---|-------------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 500 |
| Number of individual labels per row | 2 |
| Printability | Thermal transfer |
| Device | 5146477 THERMOMARK ROLL |
| | 5145274 THERMOMARK X1.1 |
| | 5146231 THERMOMARK X1.2 |
| | 5145313 THERMOMARK S1 |
| | 5146257 THERMOMARK S1.1 |
| Ink ribbon | 5145384 THERMOMARK-RIBBON 110 |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN ISO 9227:2012-09 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Foil strength | 175 µm |
| Marking mounting type | snapped into marker carrier |

Standards and Regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>