


NPN SILICON HIGH FREQUENCY TRANSISTOR

FEATURES

- **HIGH GAIN BANDWIDTH:** $f_T = 25$ GHz
- **LOW NOISE FIGURE:** $NF = 1.1$ dB at 2 GHz
- **HIGH MAXIMUM STABLE GAIN:** 20 dB at $f = 2$ GHz
- **NEW LOW PROFILE M04 PACKAGE:**
 - SOT-343 footprint, with a height of just 0.59 mm
 - Flat Lead Style for better RF performance



DESCRIPTION

NEC's NE662M04 is fabricated using NEC's UHS0 25 GHz f_T wafer process. With a typical transition frequency of 25 GHz the NE662M04 is usable in applications from 100 MHz to 10 GHz. The NE662M04 provides excellent low voltage/low current performance.

NEC's new low profile/flat lead style "M04" package is ideal for today's portable wireless applications. The NE662M04 is an ideal choice for LNA and oscillator requirements in all mobile communication systems.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

| | | PART NUMBER EIAJ ¹ REGISTERED NUMBER PACKAGE OUTLINE | NE662M04 2SC5508 M04 | | | |
|---------|-----------------|---|----------------------------|-----|------|------|
| SYMBOLS | | PARAMETERS AND CONDITIONS | UNITS | MIN | TYP | MAX |
| DC | ICBO | Collector Cutoff Current at $V_{CB} = 5\text{V}$, $I_E = 0$ | nA | | | 200 |
| | IEBO | Emitter Cutoff Current at $V_{EB} = 1\text{V}$, $I_C = 0$ | nA | | | 200 |
| | hFE | Forward Current Gain ² at $V_{CE} = 2\text{V}$, $I_C = 5\text{mA}$ | | 50 | 70 | 100 |
| RF | f_T | Gain Bandwidth at $V_{CE} = 3\text{V}$, $I_C = 30\text{mA}$, $f = 2\text{GHz}$ | GHz | 20 | 25 | |
| | MAG | Maximum Available Power Gain ⁴ at $V_{CE} = 2\text{V}$, $I_C = 20\text{mA}$, $f = 2\text{GHz}$ | dB | | 20 | |
| | MSG | Maximum Stable Gain ⁵ at $V_{CE} = 2\text{V}$, $I_C = 20\text{mA}$, $f = 2\text{GHz}$ | dB | | 20 | |
| | $ S_{21} ^2$ | Insertion Power Gain at $V_{CE} = 2\text{V}$, $I_C = 20\text{mA}$, $f = 2\text{GHz}$ | dB | 14 | 17 | |
| | NF | Noise Figure at $V_{CE} = 2\text{V}$, $I_C = 5\text{mA}$, $f = 2\text{GHz}$, $Z_{IN} = Z_{OPT}$ | dB | | 1.1 | 1.5 |
| | P_{1dB} | Output Power at 1 dB compression point at $V_{CE} = 2\text{V}$, $I_C = 20\text{mA}$, $f = 2\text{GHz}$ | dBm | | 11 | |
| | IP ₃ | Third Order Intercept Point at $V_{CE} = 2\text{V}$, $I_C = 20\text{mA}$, $f = 2\text{GHz}$ | | | 22 | |
| | Cre | Feedback Capacitance ³ at $V_{CB} = 2\text{V}$, $I_C = 0$, $f = 1\text{MHz}$ | pF | | 0.18 | 0.24 |

Notes:

1. Electronic Industrial Association of Japan.
2. Pulsed measurement, pulse width $\leq 350\ \mu\text{s}$, duty cycle $\leq 2\%$.
3. Capacitance is measured by capacitance meter (automatic balance bridge method) when emitter pin is connected to the guard pin.

$$4. \text{MAG} = \left| \frac{S_{21}}{S_{12}} \right| \left(K - \sqrt{K^2 - 1} \right)$$

$$5. \text{MSG} = \left| \frac{S_{21}}{S_{12}} \right|$$

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.

ABSOLUTE MAXIMUM RATINGS¹ (T_A = 25°C)


| SYMBOLS | PARAMETERS | UNITS | RATINGS |
|------------------|------------------------------|-------|-------------|
| V _{CB0} | Collector to Base Voltage | V | 15 |
| V _{CE0} | Collector to Emitter Voltage | V | 3.3 |
| V _{EB0} | Emitter to Base Voltage | V | 1.5 |
| I _C | Collector Current | mA | 35 |
| P _T | Total Power Dissipation | mW | 115 |
| T _J | Junction Temperature | °C | 150 |
| T _{STG} | Storage Temperature | °C | -65 to +150 |

Note:


1. Operation in excess of any one of these parameters may result in permanent damage.

TYPICAL OPTIMAL NOISE MATCHING (T_A = 25°C)

V_{CE} = 2 V, I_C = 5 mA, f = 1 GHz



V_{CE} = 2 V, I_C = 5 mA, f = 2 GHz









TYPICAL NOISE PARAMETERS (T_A = 25°C)

| FREQ. (GHz) | NF _{MIN} (dB) | G _A (dB) | Γ _{OPT} | | Rn/50 |
|--|------------------------|---------------------|------------------|--------|-------|
| | | | MAG | ANG | |
| V _C = 2 V, I _C = 3 mA | | | | | |
| 0.8 | 0.78 | 21.4 | 0.26 | 31.7 | 0.17 |
| 0.9 | 0.80 | 20.7 | 0.26 | 32.7 | 0.17 |
| 1.0 | 0.82 | 20.0 | 0.26 | 34.7 | 0.17 |
| 1.5 | 0.93 | 17.0 | 0.23 | 57.0 | 0.16 |
| 1.8 | 1.00 | 15.6 | 0.20 | 78.0 | 0.14 |
| 1.9 | 1.02 | 15.2 | 0.19 | 86.0 | 0.14 |
| 2.0 | 1.04 | 14.8 | 0.19 | 94.2 | 0.13 |
| 2.5 | 1.15 | 13.5 | 0.20 | 138.3 | 0.10 |
| V _C = 2 V, I _C = 5 mA | | | | | |
| 0.8 | 0.93 | 22.5 | 0.12 | 28.1 | 0.15 |
| 0.9 | 0.94 | 21.8 | 0.12 | 28.8 | 0.15 |
| 1.0 | 0.96 | 21.1 | 0.12 | 31.7 | 0.15 |
| 1.5 | 1.03 | 18.1 | 0.09 | 71.1 | 0.14 |
| 1.8 | 1.07 | 18.7 | 0.08 | 106.2 | 0.13 |
| 1.9 | 1.09 | 16.3 | 0.08 | 118.5 | 0.13 |
| 2.0 | 1.10 | 15.9 | 0.08 | 130.5 | 0.12 |
| 2.5 | 1.17 | 14.3 | 0.14 | -179.7 | 0.11 |
| V _C = 2 V, I _C = 10 mA | | | | | |
| 0.8 | 1.28 | 23.7 | 0.07 | -159.4 | 0.13 |
| 0.9 | 1.29 | 23.0 | 0.07 | -157.5 | 0.13 |
| 1.0 | 1.30 | 22.3 | 0.08 | -155.7 | 0.13 |
| 1.5 | 1.37 | 19.3 | 0.13 | -149.2 | 0.13 |
| 1.8 | 1.41 | 17.8 | 0.18 | -146.1 | 0.13 |
| 1.9 | 1.43 | 17.3 | 0.17 | -146.0 | 0.13 |
| 2.0 | 1.44 | 16.9 | 0.19 | -143.9 | 0.13 |
| 2.5 | 1.51 | 15.3 | 0.25 | -136.7 | 0.13 |
| V _C = 2 V, I _C = 20 mA | | | | | |
| 0.8 | 1.59 | 24.5 | 0.28 | -158.1 | 0.12 |
| 0.9 | 1.61 | 23.7 | 0.28 | -155.5 | 0.13 |
| 1.0 | 1.63 | 23.0 | 0.27 | -153.1 | 0.13 |
| 1.5 | 1.72 | 19.9 | 0.30 | -142.6 | 0.14 |
| 1.8 | 1.78 | 18.3 | 0.33 | -137.3 | 0.15 |
| 1.9 | 1.79 | 17.9 | 0.34 | -135.7 | 0.08 |
| 2.0 | 1.81 | 17.5 | 0.35 | -134.1 | 0.16 |
| 2.5 | 1.90 | 15.8 | 0.40 | -126.5 | 0.18 |







THERMAL RESISTANCE

| ITEM | SYMBOL | VALUE | UNIT |
|--------------------------------|---------------------|-------|------|
| Junction to Case Resistance | R _{th j-c} | 150 | °C/W |
| Junction to Ambient Resistance | R _{th j-a} | 650 | °C/W |

TYPICAL PERFORMANCE CURVES (TA = 25°C)




TYPICAL PERFORMANCE CURVES (T_A = 25°C)




TYPICAL PERFORMANCE CURVES (TA = 25°C)


FORWARD INSERTION GAIN vs. FREQUENCY




FORWARD INSERTION GAIN AND MAXIMUM AVAILABLE GAIN vs. FREQUENCY




FORWARD INSERTION GAIN AND MAXIMUM AVAILABLE GAIN vs. FREQUENCY




MAXIMUM STABLE GAIN, INSERTION POWER GAIN, MAXIMUM AVAILABLE GAIN vs. COLLECTOR CURRENT



MAXIMUM STABLE GAIN, INSERTION POWER GAIN, MAXIMUM AVAILABLE GAIN vs. COLLECTOR CURRENT



OUTLINE DIMENSIONS (Units in mm)



PIN CONNECTIONS

- 1. Emitter
- 2. Collector
- 3. Emitter
- 4. Base



ORDERING INFORMATION (Solder Contains Lead)

| PART NUMBER | QUANTITY | PACKAGING |
|-------------|----------|-------------|
| NE662M04-T2 | 3000 | Tape & Reel |

ORDERING INFORMATION (Pb-Free)

| PART NUMBER | QUANTITY | PACKAGING |
|---------------|----------|-------------|
| NE662M04-T2-A | 3000 | Tape & Reel |

TYPICAL SCATTERING PARAMETERS (TA = 25°C)



NE662M04

Vds = 2 V, Ids = 5 mA

| FREQUENCY GHz | S11 | | S21 | | S12 | | S22 | | K | MAG ¹ (dB) |
|------------------|-------|---------|--------|---------|-------|---------|-------|---------|------|--------------------------|
| | MAG | ANG | MAG | ANG | MAG | ANG | MAG | ANG | | |
| 0.10 | 0.800 | -6.49 | 12.912 | 170.08 | 0.010 | 80.54 | 0.975 | -12.55 | 0.14 | 31.03 |
| 0.20 | 0.823 | -20.59 | 12.309 | 162.54 | 0.019 | 73.16 | 0.908 | -19.04 | 0.17 | 28.23 |
| 0.30 | 0.784 | -33.50 | 11.948 | 153.92 | 0.026 | 66.89 | 0.878 | -24.33 | 0.19 | 26.63 |
| 0.40 | 0.756 | -44.64 | 11.513 | 146.61 | 0.033 | 61.60 | 0.844 | -29.71 | 0.21 | 25.48 |
| 0.50 | 0.723 | -54.00 | 11.004 | 139.33 | 0.038 | 56.80 | 0.798 | -35.10 | 0.26 | 24.61 |
| 0.70 | 0.673 | -71.29 | 9.884 | 126.94 | 0.047 | 49.31 | 0.717 | -43.61 | 0.34 | 23.25 |
| 1.00 | 0.606 | -94.50 | 8.378 | 111.49 | 0.056 | 40.70 | 0.626 | -53.73 | 0.45 | 21.77 |
| 1.50 | 0.525 | -125.16 | 6.529 | 91.42 | 0.065 | 32.29 | 0.529 | -65.53 | 0.63 | 20.02 |
| 2.00 | 0.481 | -149.81 | 5.267 | 75.35 | 0.071 | 27.18 | 0.473 | -74.56 | 0.79 | 18.68 |
| 2.50 | 0.452 | -171.81 | 4.390 | 61.34 | 0.077 | 23.73 | 0.437 | -82.64 | 0.94 | 17.56 |
| 3.00 | 0.443 | 168.25 | 3.750 | 48.61 | 0.083 | 20.64 | 0.414 | -90.48 | 1.05 | 15.25 |
| 3.50 | 0.447 | 149.84 | 3.263 | 36.68 | 0.088 | 17.74 | 0.399 | -98.44 | 1.13 | 13.46 |
| 4.00 | 0.462 | 133.60 | 2.881 | 25.36 | 0.095 | 14.65 | 0.390 | -106.85 | 1.18 | 12.25 |
| 5.00 | 0.503 | 106.93 | 2.323 | 3.99 | 0.108 | 7.35 | 0.391 | -124.19 | 1.21 | 10.54 |
| 6.00 | 0.533 | 85.28 | 1.941 | -15.75 | 0.122 | -0.60 | 0.407 | -138.63 | 1.21 | 9.27 |
| 7.00 | 0.561 | 64.59 | 1.663 | -34.58 | 0.136 | -10.18 | 0.414 | -150.24 | 1.19 | 8.24 |
| 8.00 | 0.597 | 44.11 | 1.458 | -53.07 | 0.151 | -20.97 | 0.396 | -161.21 | 1.17 | 7.35 |
| 9.00 | 0.648 | 25.70 | 1.289 | -71.41 | 0.164 | -32.58 | 0.365 | -175.83 | 1.13 | 6.76 |
| 10.00 | 0.701 | 10.10 | 1.150 | -89.34 | 0.176 | -44.85 | 0.338 | 165.91 | 1.06 | 6.64 |
| 11.00 | 0.742 | -3.57 | 1.033 | -107.27 | 0.186 | -57.61 | 0.322 | 147.34 | 0.99 | 7.44 |
| 12.00 | 0.770 | -17.38 | 0.937 | -125.45 | 0.195 | -71.16 | 0.291 | 132.02 | 0.96 | 6.81 |
| 13.00 | 0.800 | -32.18 | 0.852 | -144.57 | 0.202 | -86.33 | 0.220 | 115.42 | 0.96 | 6.26 |
| 14.00 | 0.832 | -47.17 | 0.761 | -164.70 | 0.199 | -101.97 | 0.130 | 84.64 | 1.01 | 5.15 |
| 15.00 | 0.864 | -60.22 | 0.669 | 174.87 | 0.191 | -117.93 | 0.095 | 15.41 | 1.06 | 3.91 |
| 16.00 | 0.886 | -71.89 | 0.586 | 154.00 | 0.179 | -134.03 | 0.128 | -38.31 | 1.13 | 2.94 |
| 17.00 | 0.893 | -83.62 | 0.505 | 131.56 | 0.161 | -150.31 | 0.183 | -80.23 | 1.37 | 1.32 |
| 18.00 | 0.893 | -95.92 | 0.432 | 109.00 | 0.142 | -165.37 | 0.273 | -113.09 | 1.78 | -0.29 |

Note:

1. Gain Calculations:



$$MAG = \frac{|S_{21}|}{|S_{12}|} (K \pm \sqrt{K^2 - 1})$$

When $K \leq 1$, MAG is undefined and MSG values are used. $MSG = \frac{|S_{21}|}{|S_{12}|}$, $K = \frac{1 + |\Delta|^2 - |S_{11}|^2 - |S_{22}|^2}{2 |S_{12} S_{21}|}$, $\Delta = S_{11} S_{22} - S_{21} S_{12}$

MAG = Maximum Available Gain

MSG = Maximum Stable Gain

TYPICAL SCATTERING PARAMETERS (TA = 25°C)



NE662M04

Vds = 2 V, Ids = 10 mA

| FREQUENCY | S11 | | S21 | | S12 | | S22 | | K | MAG ¹ |
|-----------|-------|---------|--------|---------|-------|---------|-------|---------|------|------------------|
| GHz | MAG | ANG | MAG | ANG | MAG | ANG | MAG | ANG | | (dB) |
| 0.10 | 0.656 | -12.55 | 21.524 | 167.65 | 0.009 | 79.73 | 0.953 | -15.38 | 0.17 | 33.8 |
| 0.50 | 0.558 | -72.63 | 16.388 | 130.46 | 0.032 | 54.65 | 0.704 | -43.47 | 0.39 | 27.1 |
| 1.00 | 0.459 | -117.32 | 11.085 | 102.71 | 0.045 | 44.24 | 0.505 | -61.57 | 0.64 | 23.9 |
| 1.50 | 0.411 | -147.32 | 8.116 | 84.49 | 0.055 | 40.54 | 0.416 | -71.56 | 0.83 | 21.7 |
| 2.00 | 0.390 | -170.12 | 6.357 | 70.11 | 0.064 | 37.88 | 0.371 | -79.33 | 0.95 | 19.9 |
| 2.50 | 0.380 | 169.60 | 5.209 | 57.41 | 0.074 | 34.88 | 0.345 | -86.61 | 1.04 | 17.2 |
| 3.00 | 0.384 | 151.78 | 4.404 | 45.78 | 0.084 | 31.26 | 0.329 | -94.15 | 1.10 | 15.3 |
| 3.50 | 0.396 | 135.61 | 3.812 | 34.81 | 0.093 | 27.22 | 0.318 | -102.20 | 1.13 | 13.9 |
| 4.00 | 0.417 | 121.45 | 3.357 | 24.31 | 0.103 | 22.52 | 0.313 | -110.82 | 1.14 | 12.8 |
| 4.50 | 0.441 | 109.14 | 2.999 | 14.09 | 0.112 | 17.49 | 0.312 | -119.93 | 1.15 | 11.9 |
| 5.00 | 0.462 | 98.03 | 2.707 | 4.16 | 0.121 | 12.11 | 0.316 | -128.31 | 1.14 | 11.2 |
| 5.50 | 0.478 | 88.13 | 2.466 | -5.47 | 0.129 | 6.79 | 0.323 | -135.75 | 1.14 | 10.5 |
| 6.00 | 0.489 | 78.58 | 2.270 | -14.88 | 0.138 | 1.28 | 0.331 | -141.92 | 1.14 | 9.9 |
| 6.50 | 0.502 | 69.13 | 2.100 | -24.15 | 0.145 | -4.55 | 0.338 | -147.40 | 1.13 | 9.4 |
| 7.00 | 0.516 | 59.69 | 1.958 | -33.35 | 0.153 | -10.53 | 0.336 | -152.31 | 1.12 | 8.9 |
| 7.50 | 0.533 | 50.19 | 1.835 | -42.50 | 0.160 | -16.66 | 0.329 | -157.13 | 1.12 | 8.5 |
| 8.00 | 0.552 | 40.84 | 1.724 | -51.68 | 0.166 | -22.97 | 0.314 | -161.77 | 1.12 | 8.1 |
| 8.50 | 0.578 | 32.06 | 1.624 | -60.85 | 0.172 | -29.26 | 0.298 | -167.85 | 1.11 | 7.8 |
| 9.00 | 0.606 | 23.80 | 1.533 | -70.03 | 0.177 | -35.77 | 0.279 | -175.31 | 1.09 | 7.5 |
| 9.50 | 0.635 | 16.08 | 1.448 | -79.10 | 0.182 | -42.17 | 0.262 | -176.18 | 1.07 | 7.4 |
| 10.00 | 0.662 | 9.25 | 1.373 | -88.08 | 0.186 | -48.81 | 0.249 | -167.10 | 1.04 | 7.4 |
| 10.50 | 0.687 | 2.66 | 1.303 | -97.24 | 0.190 | -55.36 | 0.238 | -157.82 | 1.02 | 7.5 |
| 11.00 | 0.708 | -3.68 | 1.240 | -106.32 | 0.193 | -62.02 | 0.228 | -150.01 | 0.99 | 8.1 |
| 11.50 | 0.725 | -10.23 | 1.180 | -115.51 | 0.196 | -68.84 | 0.216 | -143.52 | 0.98 | 7.8 |
| 12.00 | 0.740 | -16.97 | 1.129 | -124.94 | 0.198 | -75.82 | 0.196 | -139.24 | 0.97 | 7.6 |
| 12.50 | 0.759 | -23.90 | 1.078 | -134.43 | 0.200 | -82.99 | 0.165 | -136.32 | 0.96 | 7.3 |
| 13.00 | 0.778 | -31.43 | 1.026 | -144.36 | 0.200 | -90.81 | 0.130 | -133.05 | 0.96 | 7.1 |
| 13.50 | 0.797 | -39.26 | 0.971 | -154.44 | 0.197 | -98.62 | 0.089 | -132.98 | 0.97 | 6.9 |
| 14.00 | 0.817 | -46.37 | 0.917 | -164.53 | 0.193 | -105.96 | 0.043 | -134.60 | 0.99 | 6.8 |
| 14.50 | 0.836 | -53.18 | 0.862 | -174.70 | 0.189 | -113.50 | 0.008 | -126.17 | 1.00 | 6.2 |
| 15.00 | 0.854 | -59.55 | 0.809 | -175.14 | 0.184 | -121.17 | 0.045 | -78.36 | 1.02 | 5.5 |
| 15.50 | 0.870 | -65.38 | 0.760 | -164.91 | 0.178 | -128.62 | 0.074 | -82.90 | 1.03 | 5.3 |
| 16.00 | 0.879 | -71.31 | 0.714 | -154.41 | 0.171 | -136.43 | 0.100 | -92.08 | 1.07 | 4.6 |
| 16.50 | 0.883 | -77.25 | 0.668 | -143.35 | 0.163 | -144.44 | 0.126 | -102.52 | 1.16 | 3.7 |
| 17.00 | 0.888 | -83.09 | 0.622 | -132.27 | 0.153 | -152.15 | 0.161 | -113.78 | 1.27 | 3.0 |
| 17.50 | 0.891 | -89.24 | 0.576 | -121.03 | 0.143 | -159.23 | 0.204 | -124.99 | 1.43 | 2.2 |
| 18.00 | 0.890 | -95.45 | 0.539 | -110.25 | 0.134 | -166.19 | 0.250 | -133.10 | 1.60 | 1.5 |

Note:



1. Gain Calculations:

$$MAG = \frac{|S_{21}|}{|S_{12}|} (K \pm \sqrt{K^2 - 1}). \text{ When } K \leq 1, \text{ MAG is undefined and MSG values are used. } MSG = \frac{|S_{21}|}{|S_{12}|}, K = \frac{1 + |\Delta|^2 - |S_{11}|^2 - |S_{22}|^2}{2 |S_{12} S_{21}|}, \Delta = S_{11} S_{22} - S_{21} S_{12}$$

MAG = Maximum Available Gain

MSG = Maximum Stable Gain

TYPICAL SCATTERING PARAMETERS (TA = 25°C)



NE662M04

Vds = 2 V, Ids = 20 mA

| FREQUENCY GHz | S11 | | S21 | | S12 | | S22 | | K | MAG ¹ (dB) |
|------------------|-------|---------|--------|---------|-------|---------|-------|---------|------|--------------------------|
| | MAG | ANG | MAG | ANG | MAG | ANG | MAG | ANG | | |
| 0.10 | 0.478 | -21.17 | 30.628 | 164.59 | 0.008 | 77.90 | 0.920 | -18.24 | 0.27 | 35.8 |
| 0.50 | 0.420 | -95.65 | 20.411 | 122.80 | 0.027 | 55.26 | 0.608 | -50.41 | 0.54 | 28.8 |
| 1.00 | 0.377 | -140.33 | 12.654 | 96.57 | 0.039 | 50.55 | 0.413 | -66.91 | 0.81 | 25.1 |
| 1.50 | 0.361 | -167.18 | 8.963 | 79.99 | 0.051 | 48.74 | 0.338 | -75.34 | 0.96 | 22.5 |
| 2.00 | 0.356 | 173.00 | 6.924 | 66.76 | 0.063 | 45.98 | 0.304 | -82.29 | 1.03 | 19.4 |
| 2.50 | 0.356 | 155.15 | 5.625 | 54.91 | 0.075 | 42.06 | 0.287 | -89.18 | 1.08 | 17.1 |
| 3.00 | 0.366 | 139.53 | 4.733 | 43.94 | 0.087 | 37.36 | 0.276 | -96.76 | 1.10 | 15.4 |
| 3.50 | 0.383 | 125.38 | 4.086 | 33.53 | 0.098 | 32.17 | 0.268 | -105.14 | 1.12 | 14.1 |
| 4.00 | 0.405 | 112.90 | 3.595 | 23.51 | 0.109 | 26.52 | 0.265 | -114.14 | 1.12 | 13.1 |
| 4.50 | 0.429 | 101.89 | 3.211 | 13.68 | 0.120 | 20.61 | 0.266 | -123.63 | 1.12 | 12.2 |
| 5.00 | 0.449 | 91.80 | 2.900 | 4.06 | 0.129 | 14.46 | 0.271 | -132.09 | 1.11 | 11.5 |
| 5.50 | 0.464 | 82.65 | 2.645 | -5.30 | 0.138 | 8.45 | 0.278 | -139.34 | 1.11 | 10.8 |
| 6.00 | 0.474 | 73.73 | 2.438 | -14.52 | 0.147 | 2.28 | 0.285 | -145.15 | 1.10 | 10.2 |
| 6.50 | 0.485 | 64.85 | 2.260 | -23.66 | 0.155 | -4.15 | 0.291 | -150.18 | 1.10 | 9.7 |
| 7.00 | 0.498 | 55.95 | 2.109 | -32.75 | 0.163 | -10.60 | 0.287 | -154.60 | 1.09 | 9.2 |
| 7.50 | 0.514 | 47.03 | 1.978 | -41.81 | 0.170 | -17.22 | 0.279 | -158.90 | 1.09 | 8.8 |
| 8.00 | 0.533 | 38.18 | 1.861 | -50.95 | 0.176 | -23.96 | 0.262 | -162.87 | 1.09 | 8.4 |
| 8.50 | 0.558 | 29.93 | 1.755 | -60.07 | 0.181 | -30.61 | 0.244 | -168.45 | 1.09 | 8.1 |
| 9.00 | 0.586 | 22.10 | 1.658 | -69.20 | 0.186 | -37.43 | 0.224 | -175.58 | 1.07 | 7.8 |
| 9.50 | 0.616 | 14.75 | 1.568 | -78.26 | 0.190 | -44.07 | 0.206 | -176.14 | 1.06 | 7.7 |
| 10.00 | 0.643 | 8.23 | 1.489 | -87.24 | 0.194 | -50.92 | 0.191 | -167.23 | 1.04 | 7.6 |
| 10.50 | 0.669 | 1.93 | 1.415 | -96.42 | 0.196 | -57.75 | 0.178 | -158.39 | 1.02 | 7.7 |
| 11.00 | 0.691 | -4.15 | 1.347 | -105.57 | 0.198 | -64.56 | 0.166 | -151.79 | 1.00 | 8.2 |
| 11.50 | 0.709 | -10.52 | 1.286 | -114.82 | 0.200 | -71.54 | 0.153 | -147.66 | 0.99 | 8.1 |
| 12.00 | 0.725 | -17.06 | 1.229 | -124.30 | 0.201 | -78.71 | 0.135 | -147.52 | 0.98 | 7.9 |
| 12.50 | 0.746 | -23.83 | 1.172 | -133.88 | 0.202 | -85.96 | 0.110 | -151.92 | 0.97 | 7.6 |
| 13.00 | 0.766 | -31.30 | 1.115 | -143.85 | 0.200 | -93.76 | 0.084 | -160.86 | 0.97 | 7.5 |
| 13.50 | 0.787 | -39.12 | 1.055 | -153.89 | 0.196 | -101.42 | 0.066 | -176.40 | 0.98 | 7.3 |
| 14.00 | 0.809 | -46.23 | 0.996 | -163.89 | 0.191 | -108.56 | 0.063 | -144.57 | 0.99 | 7.2 |
| 14.50 | 0.829 | -53.03 | 0.936 | -173.90 | 0.186 | -115.98 | 0.078 | -121.33 | 1.00 | 6.6 |
| 15.00 | 0.847 | -59.39 | 0.879 | -176.00 | 0.180 | -123.53 | 0.102 | -112.73 | 1.02 | 6.0 |
| 15.50 | 0.864 | -65.18 | 0.828 | -165.89 | 0.173 | -130.77 | 0.122 | -114.28 | 1.03 | 5.8 |
| 16.00 | 0.875 | -71.13 | 0.779 | -155.45 | 0.166 | -138.24 | 0.141 | -119.68 | 1.06 | 5.2 |
| 16.50 | 0.879 | -77.09 | 0.731 | -144.58 | 0.158 | -146.13 | 0.160 | -127.09 | 1.14 | 4.4 |
| 17.00 | 0.885 | -82.91 | 0.681 | -133.70 | 0.148 | -153.64 | 0.188 | -133.94 | 1.24 | 3.7 |
| 17.50 | 0.888 | -89.06 | 0.633 | -122.64 | 0.137 | -160.49 | 0.225 | -141.26 | 1.40 | 2.9 |
| 18.00 | 0.887 | -95.33 | 0.595 | -112.04 | 0.129 | -167.16 | 0.263 | -146.76 | 1.56 | 2.2 |

Note:

1. Gain Calculations:

$$MAG = \frac{|S_{21}|}{|S_{12}|} (K \pm \sqrt{K^2 - 1})$$


When $K \leq 1$, MAG is undefined and MSG values are used. $MSG = \frac{|S_{21}|}{|S_{12}|}$, $K = \frac{1 + |\Delta|^2 - |S_{11}|^2 - |S_{22}|^2}{2 |S_{12} S_{21}|}$, $\Delta = S_{11} S_{22} - S_{21} S_{12}$

MAG = Maximum Available Gain

MSG = Maximum Stable Gain

NE662M04 NONLINEAR MODEL

SCHEMATIC



BJT NONLINEAR MODEL PARAMETERS (1)

| Parameters | Q1 | Parameters | Q1 |
|------------|---------|------------|-------|
| IS | 1.6e-16 | MJC | 0.3 |
| BF | 111 | XCJC | 0.3 |
| NF | 1.02 | CJS | 0 |
| VAF | 23 | VJS | 0.75 |
| IKF | 0.38 | MJS | 0 |
| ISE | 1e-6 | FC | 0.55 |
| NE | 30 | TF | 3e-12 |
| BR | 12 | XTF | 0.1 |
| NR | 1.02 | VTF | 0.8 |
| VAR | 2.5 | ITF | 0.14 |
| IKR | 0.1 | PTF | 23.5 |
| ISC | 3e-15 | TR | 1e-11 |
| NC | 1.28 | EG | 1.11 |
| RE | 0.77 | XTB | 0 |
| RB | 3.5 | XTI | 3 |
| RBM | 20 | KF | 0 |
| IRB | 1.3e-3 | AF | 1 |
| RC | 8.75 | | |
| CJE | 0.4e-12 | | |
| VJE | 0.6 | | |
| MJE | 0.5 | | |
| CJC | 0.1e-12 | | |
| VJC | 0.75 | | |

(1) Gummel-Poon Model

UNITS

| Parameter | Units |
|-------------|---------|
| time | seconds |
| capacitance | farads |
| inductance | henries |
| resistance | ohms |
| voltage | volts |
| current | amps |

ADDITIONAL PARAMETERS

| Parameters | NE662M04 |
|------------|-----------|
| CCB | 0.09e-12 |
| CCE | 0.09e-12 |
| LB | 1.0e-9 |
| LC | 0.6e-9 |
| LE | 0.22e-9 |
| CCBPKG | 0.001e-12 |
| CCEPKG | 0.3e-12 |
| CBEPK | 0.21e-12 |
| LBX | 0.2e-9 |
| LCX | 0.2e-9 |
| LEX | 0.07e-9 |

MODEL RANGE

Frequency: 0.1 to 12 GHz
 Bias: VCE = 0.5 V to 3 V, IC = 1 mA to 20 mA
 Date: 01/12/2000

Life Support Applications

These NEC products are not intended for use in life support devices, appliances, or systems where the malfunction of these products can reasonably be expected to result in personal injury. The customers of CEL using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CEL for all damages resulting from such improper use or sale.

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL’s understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

| Restricted Substance per RoHS | Concentration Limit per RoHS (values are not yet fixed) | Concentration contained in CEL devices | |
|-------------------------------|---|--|-----|
| | | -A | -AZ |
| Lead (Pb) | < 1000 PPM | Not Detected | (*) |
| Mercury | < 1000 PPM | Not Detected | |
| Cadmium | < 100 PPM | Not Detected | |
| Hexavalent Chromium | < 1000 PPM | Not Detected | |
| PBB | < 1000 PPM | Not Detected | |
| PBDE | < 1000 PPM | Not Detected | |

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

Important Information and Disclaimer: Information provided by CEL on its website or in other communications concerning the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall CEL’s liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.

See CEL Terms and Conditions for additional clarification of warranties and liability.