

IM100

TTL to RS232 translator



Features

- ❖ Converts 5V / 3.3V signals to RS232 levels
- ❖ Compact size (the size as mini mouse)
- ❖ Powers from target's 5V or 3.3V supply
- ❖ Supports RS232 speeds of up to 1 mega bits per seconds

Dimension:

Length, 64.65 mm

Width, 43.11 mm

Height, 20.41 mm

How to reach us

Interface Masters, Inc.

2381 Zanker Road, Suite 130

San Jose, CA 95131

Phone: 408-456-2545 x10

Fax: 815-364-0888

E-mail: info@interfacemasters.com

Home page: <http://www.interfacemasters.com>

Pigtail female connector:

Manufacturer	Molex
Part number	50-57-9204
Mating connector	100 mil center male header

Signal	Pin 1	Pin 2	Pin 3	Pin 4
Description	3.3V or 5V	Transmit data	Receive Date	GND
Direction	Target provides power	From target to remote RS232 device	From remote RS232 device to target	Target

Pigtail female connector pin out

Nine pin DSUB connector

Configuration:	DTE¹
Gender:	Male²

Signal	Pin 2	Pin 3	Pin 5
Description	Transmit data	Receive Date	GND
Direction	From target to remote RS232 device	From remote RS232 device to target	

DB9 Connector pin out

¹ DCE configuration available on special request

² Female connectors are available on special request