





Metallized Polypropylene Capacitors



(All dimensions in inches)



1213EFR

**Epoxy Case
(Radial Leads)**

Lead Specs.
Tinned Copperweld
B through E cases: 22 AWG
F through Q cases: 20 AWG

DIMENSIONS and RATINGS

Cap. μF	63/40 VDC/VAC	160/100 VDC/VAC	250/160 VDC/VAC	400/220 VDC/VAC	630/250 VDC/VAC	CASE SIZE	L $\frac{\text{mm}}{\text{in.}}$	T $\frac{\text{mm}}{\text{in.}}$	H $\frac{\text{mm}}{\text{in.}}$	S $\frac{\text{mm}}{\text{in.}}$
.001	B	B	B	B	C	B	10.5	4	9	7.5
.0012	B	B	B	B	C	C	.413	.157	.354	.295
.0015	B	B	B	B	C		13	4	9	10
.0018	B	B	B	B	C	D	.512	.157	.354	.394
.0022	B	B	B	B	C		13	5	11	10
.0027	B	B	B	B	C	E	.512	.197	.433	.394
.0033	B	B	B	B	C		13	6	12	10
.0039	B	B	B	B	C	F	.512	.236	.472	.394
.0047	B	B	B	B	C		18	5	11	15
.0056	B	B	B	B	C	G	.709	.197	.433	.591
.0068	B	B	B	B	C		18	6	12	15
.0082	B	B	B	C	C	H	.709	.236	.472	.591
.01	B	B	B	C	D		18	7.5	13.5	15
.012	B	B	B	C	D	J	.709	.295	.531	.591
.015	B	B	C	C	E		26.5	6	15	20
.018	B	C	C	C	E	K	1.04	.236	.591	.787
.022	B	C	C	D	F		26.5	7	16	20
.027	B	C	C	D	F	L	1.04	.276	.630	.787
.033	C	C	D	E	G		26.5	6	15	22.5
.039	C	C	D	E	H	M	1.04	.236	.591	.886
.047	C	D	E	F	H		26.5	7	16	22.5
.056	C	D	E	G	H	N	1.04	.276	.630	.886
.068	D	E	E	G	K/M		26.5	8.5	16.3	22.5
.082	D	E	G	H	N	O	1.04	.335	.642	.886
.1	E	F	G	H	N		26.5	10	19	22.5
.12	E	G	G	K/M	O	P	1.04	.394	.748	.886
.15	F	G	H	K/M	P		32	11	20	27.5
.18	F	H	H	N	P	Q	1.26	.433	.787	1.08
.22	G	H	H	N	P		32	13	22	27.5
.27	G	K/M	K/M	O	Q	1.26	.512	.866	1.08	
.33	H	K/M	K/M	P						
.39	H	N	N	P						
.47	J/L	N	O	P						
.56	K/M	O	O	Q						
.68	N	P	P							
.82	O	P	Q							
1.0	O	P								
1.2	P	Q								
1.5	Q									

ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park * 41 Interstate Lane * WATERBURY, CONNECTICUT 06705

Phone (203) 755-5629

FAX (203) 755-0659