


Surface Mount Multilayer Ceramic Chip Capacitors for High Reliability Applications



FEATURES

- Made with a combination of design, materials and tight process control to achieve very high field reliability
- Surface mount, wet build process
- Reliable Noble Metal Electrode (NME) system
- MIL-PRF-55681 qualified production line. Reliability maintenance testing to verify consistent quality. (X5R max. test temperature: + 85 °C)
- Available with group A and C screening
- Available with group A screening only
- Available with Voltage Conditioning only
- Customized certification available on request to meet your quality requirements
- Available with tin-lead barrier terminations order code "L"
- Compliant to RoHS directive 2002/95/EC
- Halogen-free according to IEC 61249-2-21 definition



Available
RoHS*
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- System critical medical applications
- Mission critical military and aerospace applications

ELECTRICAL SPECIFICATIONS

Note

Electrical characteristics at + 25 °C unless otherwise specified

Operating Temperature:

X5R: - 55 °C to + 85 °C

X7R: - 55 °C to + 125 °C

Capacitance Range: 100 pF to 6.8 μF

Voltage Range: 6.3 Vdc to 500 Vdc

Temperature Coefficient of Capacitance (TCC):

X5R: ± 15 % from - 55 °C to + 85 °C, with 0 Vdc applied

X7R: ± 15 % from - 55 °C to + 125 °C, with 0 Vdc applied

Dissipation Factor:

6.3 V, 10 V ratings: 5 % max. at 1.0 V_{rms} and 1 kHz

16 V, 25 V ratings: 3.5 % max. at 1.0 V_{rms} and 1 kHz

≥ 50 V ratings: 2.5 % max. at 1.0 V_{rms} and 1 kHz

Aging Rate: 1 % maximum per decade

Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 MΩ minimum or 1000 ΩF, whichever is less

At + 125 °C and rated voltage 10 000 MΩ minimum or 100 ΩF, whichever is less

Dielectric Strength Test:

Performed per Method 103 of EIA-198-2-E.

Applied test voltages:

≤ 500 Vdc - rated: at 200 % of rated voltage

* Pb containing terminations are not RoHS compliant, exemptions may apply


VJ High Rel X7R/X5R



Vishay Vitramon

Surface Mount Multilayer Ceramic Chip Capacitors
for High Reliability Applications

DIMENSIONS in inches [millimeters]



PART ORDERING NUMBER	LENGTH (L)	WIDTH (W)	MAXIMUM THICKNESS (T)	TERMINATION PAD (P)	
				MINIMUM	MAXIMUM
VJ0402	0.040 ± 0.004 [1.00 ± 0.10]	0.020 ± 0.004 [0.50 ± 0.10]	0.024 [0.61]	0.004 [0.10]	0.016 [0.41]
VJ0603	0.063 ± 0.005 [1.60 ± 0.12]	0.031 ± 0.005 [0.80 ± 0.12]	0.036 [0.92]	0.012 [0.30]	0.018 [0.46]
VJ0805	0.079 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.053 [1.35]	0.010 [0.25]	0.028 [0.71]
VJ1206	0.126 ± 0.008 [3.20 ± 0.20]	0.063 ± 0.008 [1.60 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
VJ1210	0.126 ± 0.008 [3.20 ± 0.20]	0.098 ± 0.008 [2.50 ± 0.20]	0.067 [1.70]	0.010 [0.25]	0.028 [0.71]
VJ1808	0.180 ± 0.010 [4.57 ± 0.25]	0.080 ± 0.010 [2.03 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
VJ1812	0.177 ± 0.010 [4.50 ± 0.25]	0.126 ± 0.008 [3.20 ± 0.20]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
VJ1825	0.177 ± 0.010 [4.50 ± 0.25]	0.252 ± 0.010 [6.40 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
VJ2220	0.220 ± 0.008 [5.59 ± 0.20]	0.200 ± 0.008 [5.08 ± 0.20]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
VJ2225	0.220 ± 0.008 [5.59 ± 0.20]	0.250 ± 0.010 [6.35 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
VJ3640	0.360 ± 0.015 [9.14 ± 0.38]	0.400 ± 0.015 [10.2 ± 0.38]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]

ORDERING INFORMATION

VJ120	Y	104	J	L	A	A	T	## (2)
CASE CODE	DIELECTRIC	CAPACITANCE NOMINAL CODE	CAPACITANCE TOLERANCE	TERMINATION	DC VOLTAGE RATING (1)	MARKING	PACKAGING	PROCESS CODE
0402 0603 0805 1206 1210 1808 1812 1825 2220 2225 3640	G = X5R Y = X7R	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. Examples: 104 = 100 000 pF	J = ± 5 % K = ± 10 % M = ± 20 %	X = Ni barrier 100 % tin plated F = Silver Palladium L = Ni barrier with tin lead plated finish min. 4 % lead F = Silver palladium N = Non-magnetic	Y = 6.3 V Q = 10 V J = 16 V X = 25 V A = 50 V K = 75 V B = 100 V C = 200 V P = 250 V E = 500	A = Unmarked	C = 7" reel/paper tape T = 7" reel/plastic tape P = 11 1/4" reel/paper tape R = 11 1/4" reel/plastic tape B = Bulk W = Waffle tray (Paper tape for 0402 and 0603 only)	2L = High Rel group A and C screening 68 = High Rel group A screening only 5G = Voltage conditioning only

Notes

(1) DC voltage rating should not be exceeded in application

(2) Process code with 2 digits has to be added







HIGH REL X7R/X5R																																
EIA CODE		0402						0603						0805						1206					1210 ⁽¹⁾							
VOLTAGE (Vdc)		6.3	10	16	25	50	100	6.3	10	16	25	50	100	10	16	25	50	100	200	16	25	50	100	200	500	16	25	50	75	100	200	500
VOLTAGE CODE		Y	Q	J	X	A	B	Y	Q	J	X	A	B	Q	J	X	A	B	C	J	X	A	B	C	E	J	X	A	K	B	C	E
CAP. CODE	CAP.																															
101	100 pF	•	•	•	•	•	•																									
121	120 pF	•	•	•	•	•	•																									
151	150 pF	•	•	•	•	•	•																									
181	180 pF	•	•	•	•	•	•																									
221	220 pF	•	•	•	•	•	•																									
271	270 pF	•	•	•	•	•	•	•	•	•	•	•	•																			
331	330 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•													
391	390 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
471	470 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
561	560 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
681	680 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
821	820 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
102	1000pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
122	1200 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
152	1500 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
182	1800 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
222	2200 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
272	2700 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
332	3300 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
392	3900 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
472	4700 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
562	5600 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
682	6800 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
822	8200 pF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
103	0.010 μF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
123	0.012 μF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
153	0.015 μF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
183	0.018 μF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
223	0.022 μF	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
273	0.027 μF	X5R	X5R	X5R				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
333	0.033 μF	X5R	X5R	X5R				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
393	0.039 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
473	0.047 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
563	0.056 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
683	0.068 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
823	0.082 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
104	0.10 μF	X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
124	0.12 μF							X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
154	0.15 μF							X5R						•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
184	0.18 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
224	0.22 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
274	0.27 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
334	0.33 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
394	0.39 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
474	0.47 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
564	0.56 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
684	0.68 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
824	0.82 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
105	1.0 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
125	1.2 μF													•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Note

⁽¹⁾ See soldering recommendations within this data book, or visit: www.vishay.com/doc?45034



HIGH REL X7R/X5R DIELECTRIC - TYPICAL PARAMETERS



STANDARD PACKAGING QUANTITIES (1)(2)(3)

BODY SIZE	TAPE SIZE	7" REEL QUANTITIES			11 1/4" AND 13" REEL QUANTITIES		BULK QUANTITIES	
		PAPER TAPE PACKAGING CODE "C"	PLASTIC TAPE PACKAGING CODE "T"	PLASTIC TAPE PACKAGING CODE "J"	PAPER TAPE PACKAGING CODE "P"	PLASTIC TAPE PACKAGING CODE "R"	VIAL PACKAGING CODE "B"	WAFFLE PACKAGING CODE "W"
0402	8 mm	5000	N/a	N/a	10 000	N/a	5000	N/a
0603	8 mm	4000	N/a	N/a	10 000	N/a	5000	N/a
0805 (4)	8 mm	3000	3000	N/a	10 000	10 000	5000	N/a
1206	8 mm	N/a	3000	N/a	N/a	10 000	5000	N/a
1210	8 mm	N/a	3000	N/a	N/a	10 000	5000	N/a
1808	12 mm	N/a	3000	N/a	N/a	10 000	1000	N/a
1812	12 mm	N/a	1000	N/a	N/a	5000	1000	N/a
1825	12 mm	N/a	1000	N/a	N/a	5000	1000	1000
2220	12 mm	N/a	1000	N/a	N/a	5000	N/a	1000
2225	12 mm	N/a	1000	N/a	N/a	5000	N/a	1000
3640	16 mm	N/a	1000	500	N/a	5000	N/a	1000

Notes

- (1) Vishay Vitramon uses embossed plastic carrier tape
- (2) REFERENCE: EIA standard RS 481 - "Taping of Surface Mount Components for Automatic Placement"
- (3) N/a = Not available
- (4) Packaging "C/P" and "T/R" depend on product thickness



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.