







PAD	CONNECTION
1	Not connected or Enable/Disable
2	Ground
3	Output
4	Supply



Scale 3:1

Features

-  **Military temperature range option**
-  **Excellent shock & vibration resistance**
-  **Enable / disable tristate option (> 1.0MHz)**
-  **Wide frequency range available**

Standard Frequencies

Frequencies in MHz				
10.00000	19.20000	48.00000	64.00000	90.00000
10.15000	19.66080	49.15200	65.00000	96.00000
10.23000	20.00000	50.00000	65.53600	98.30400
10.24000	22.11840	50.75000	66.35520	100.00000
11.05920	24.00000	51.15000	72.00000	102.40000
12.00000	25.00000	51.20000	73.72800	104.00000
12.28800	32.00000	52.00000	76.80000	131.07200
12.80000	32.76800	55.29600	78.00000	132.71040
13.00000	36.86400	58.98240	80.00000	144.00000
14.74560	40.00000	60.00000	81.20000	150.00000
16.00000	40.60000	60.90000	81.84000	160.00000
16.38400	40.96000	61.38000	81.92000	
18.43200	44.23680	61.44000	88.47360	

Binary divisions of the above frequencies also available.

Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance

Specifications

MCSO1V: 400kHz ~ 20.0MHz

MCSO1HV: 20.0 ~ 160MHz

Parameters	Product		Option Codes
	MCSO1V	MCSO1HV	
Frequency range: 400kHz ~ 20.0MHz 20.0 ~ 160MHz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Frequency stability*: ±100ppm ±50ppm tighter stabilities on request	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	T specify
Operating temperature range: 0 to +70°C -40 to +85°C -55 to +125°C	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	A B C
Operable temperature range: -55 to +125°C	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Storage temperature range: -65 to +125°C	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Supply voltage (V_{DD}): +3.3V (±10%)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Supply current (max): 10mA 30mA	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Driving ability: CMOS	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Logic levels: '0' level = +0.4V max '1' level = 90%V _{DD} min	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Start up time: 5ms max	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Waveform symmetry: 40:60 max @ 50%V _{DD}	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Rise / fall times: 7ns max 3ns max	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Enable / disable function: None (pad 1 NC) Tristate* (control via pad 1) * not available under 1.0MHz	<input checked="" type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/>	E
Shock resistance: 5,000G, 0.3ms, ½ sine	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Vibration resistance: 10G rms 10.0 ~ 2,000Hz	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Soldering condition: 260°C, 10 sec max	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	

Standard. Optional - Please specify required code(s) when ordering

* Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change and ageing over 10 years.

Ordering Information

Product name + option codes (if any) + frequency

eg: **MCSO1V/TBE 16.0MHz** ±50ppm -40 to +85°C Enable / disable

MCSO1HV/C 81.840MHz ±100ppm -55to +125°C

Option code X (eg MCSO1V/X) denotes a custom specification.

- ◆ Available on T&R (1k pcs/reel) or trays (50pcs/tray).
- ◆ Refer to our website for T&R and soldering details.