


RF PIN Diodes - Dual, Common Cathode in SOT-323

Description

Characterized by low reverse Capacitance the PIN Diodes BAR64V-05W-V was designed for RF signal switching and tuning. As a function of the forward bias current the forward resistance (RF) can be adjusted over a wide range. A long carrier life time offers low signal distortion for signals over 10 MHz up to 3 GHz. Typical applications for these PIN Diodes are switches and attenuators in wireless, mobile and TV-systems.



Features

- High voltage current controlled RF resistor
- Small diode capacitance
- Low series inductance
- Low forward resistance
- Improved performance due to two separate dice
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT

Mechanical Data

Case: SOT-323

Weight: approx. 5.7 mg

Packaging Codes/Options:

GS18/10K per 13" reel (8 mm tape), 10K/box

GS08/3K per 7" reel (8 mm tape), 15K/box

Applications

- For frequencies up to 3 GHz
- RF-signal tuning
- Signal attenuator and switches
- Mobile, wireless and TV-Applications

Parts Table

Part	Ordering code	Marking	Remarks
BAR64V-05W-V	BAR64V-05W-V-GS18 or BAR64V-05W-V-GS08	DW5	Tape and reel

Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Reverse voltage		V_R	100	V
Forward current		I_F	100	mA
Junction temperature		T_j	150	$^{\circ}\text{C}$
Storage temperature range		T_{stg}	- 55 to + 150	$^{\circ}\text{C}$

Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Min.	Typ.	Max.	Unit
Reverse voltage	$I_R = 10\text{ }\mu\text{A}$	V_R	100			V
Reverse current	$V_R = 50\text{ V}$	I_R			50	nA
Forward voltage	$I_F = 50\text{ mA}$	V_F			1.1	V
Diode capacitance	$f = 1\text{ MHz}, V_R = 0$	C_D		0.5		pF
	$f = 1\text{ MHz}, V_R = 1\text{ V}$	C_D		0.37	0.5	pF
	$f = 1\text{ MHz}, V_R = 20\text{ V}$	C_D		0.23	0.35	pF
Forward resistance	$f = 100\text{ MHz}, I_F = 1\text{ mA}$	r_f		10	20	Ω
	$f = 100\text{ MHz}, I_F = 10\text{ mA}$	r_f		2.0	3.8	Ω
	$f = 100\text{ MHz}, I_F = 100\text{ mA}$	r_f		0.8	1.35	Ω
Charge carrier life time	$I_F = 10\text{ mA}, I_R = 6\text{ mA}, i_{rr} = 3\text{ mA}$	t_{rr}		1.8		μs
Series inductance		L_S		1		nH

Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Figure 1. Forward Resistance vs. Forward Current




Figure 3. Forward Current vs. Forward Voltage




Figure 2. Diode Capacitance vs. Reverse Voltage




Figure 4. Typical Charge Recovery Curve




Figure 5. Insertion Loss of One Diode Inserted in Series with 50 Ω Strip Line




Figure 6. Isolation of One Diode Inserted in Series with 50 Ω Strip Line





Figure 7. Second Order Intercept Point for One Diode Inserted in 50 Ω Strip Line

BAR64V-05W-V




Vishay Semiconductors

Package Dimensions in millimeters (inches): SOT-323



foot print recommendation:



Document no.: 6.541-5040.02-4
Rev. 1 - Date: 06. April 2010
21113



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.