

Part Number: C1608

Revision Level: 3

Date: 11/21/2007

8C 16 AWG 65/34 TC RUBBER OAS CAROLPRENE*

CONTROL CABLE

A. CONSTRUCTION

Conductor: #16 AWG 65/34 Tinned Copper
 Insulation: 0.025" Wall Rubber
 Cable: 8 conductors @ 4.00" LHL with jute filler
 & overall mylar wrap.
 Braid #36 AWG Tinned Copper
 80% Min. coverage
 Tape: Cotton Separator
 Jacket: 0.040" Wall Carolprene* - Black
 Print Legend: *CAROL C-1608A VW-1 MADE IN USA*

DIAMETERS

0.060" nom.
 0.110" nom.
 0.400" nom.
 0.420" nom.
 0.430" nom.
 0.510" +/- 0.026"

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE: 60 C
 SUGGESTED WORKING VOLTAGE (Vrms): 300Vrms
 CONDUCTOR D.C. RESISTANCE: 4.5 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown
7	Yellow
8	Orange