# BGA Heat Sink (High Aspect Ratio Ext.) **Custom Pin Fin**



ATS Part#:

Description:

Heat Sink Type: **Custom Pin Fin** 

ATS060060011-PF-16J

60.00 x 60.00 x 11.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

Heat Sink Attachment: Equivalent Part Number: N/A

N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.14 °C/W	2.5 °C/W	1.9 °C/W	1.6 °C/W	1.4 °C/W	1.3 °C/W	1.2 °C/W
	Ducted Flow	1.5	1.2	1.1	1	0.9	0.8	0.8

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
alta	60.00 mm	60.00 mm	11.00 mm	60 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimensior</li> <li>Dimensior</li> <li>Thermal p application</li> <li>ATS reserver</li> <li>performan</li> <li>ATS certification</li> </ul>	D is fin tip to fin tip erformance data are n. ves the right to upda ce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice -6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA