


## ■ 15" TFT Open Frame Industrial Display Monitor



OPD-215



OPD-215AR

## Features

- 15" TFT XGA LCD
- Stainless Steel Open-Frame Architecture With IP-65 Certified Aluminum Front Panel
- RGB, Composite Video, S-Video, DVI Input Signal Selectable
- Supports Picture-In-Picture Function
- VESA 75mm Standard Screw Holes




## Specifications

System	
Input Signal	RGB, Composite video, S-Video
On Screen Display Control	Brightness, Contrast, Phase, Sharpness, AutoTune, PIP, H/V-position
OS Support	MS DOS, Windows® 2000, Windows® XP, Linux Redhat 8.0, Windows® 7
Mechanical	
Construction	Stainless steel chassis & aluminum alloy front panel
Front Panel Color	RAL 7035
Mounting	Panelmount, Rearmount or Rackmount Optional: Wallmount kit, Swivel ARM, Desktop stand
Dimension	Without bezel: 16.9" (W) x 12.6" (H) x 2.1" (D) (428mm x 320mm x 53.3mm) Standard bezel: 17.5" (W) x 13.2" (H) x 2.3" (D) (444mm x 336mm x 59.3mm) Rack bezel: 19.0" (W) x 13.97" (H) x 2.3" (D) (483mm x 354.8mm x 59.3mm)
Carton Dimension	23.2" (W) x 21.4" (H) x 9.2" (D) (590mm x 545mm x 236mm)
Gross Weight	Without bezel: 26.2 lb (11.9 Kg) Standard bezel: 28.4 lb (12.9 Kg) Rack bezel: 28.9 lb (13.1 Kg)
Environmental	
Operating Temperature	32°F ~ 113°F (0°C ~ 45°C)
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Operating Humidity	10% to 90% @ 40°C, non-condensing, without TouchScreen
Vibration	1G / 5 ~ 500Hz (Random) / Operation
Shock	15G peak acceleration (11 msec. duration) / Operation
EMC	CE/FCC Class A
Power Supply	
External Power Adapter 60W	Input: 100 to 240 ±10%V AC, Full Range Output: +12V DC @ 5A
LCD	
Display Type	15" color TFT LCD
Max. Resolution	1024 x 768
Max. Colors	16.2M
Dot Size	0.297mm x 0.297mm
Luminance	250 cd/m² (TYP)
Viewing Angle	150°(H) / 145°(V)
Brightness Control	Yes
Back Light MTBF (Hours)	50,000
TouchScreen (Optional)	
Type	5-wire, Analog Resistive
Resolution	2048 x 2048
Light Transmission	75%
Lifetime	35 million activations
OS Support	MS-DOS, Windows® 2000, Windows® XP, Linux Redhat 8.0, Windows® 7

# OPD-215A

## Dimension

Unit: mm



## Ordering Information

- **TF-OPD-215A-G1-1010**  
15" SVGA TFT Display Monitor
- **TF-OPD-215AT-G1-1010**  
TF-OPD-215A-G1-1010 with Resistive TouchScreen
- **TF-OPD-215AB-G1-1010**  
TF-OPD-215A-G1-1010 with Standard Bezel
- **TF-OPD-215ABT-G1-1010**  
TF-OPD-215AB-G1-1010 with Resistive TouchScreen
- **TF-OPD-215AR-G1-1010**  
TF-OPD-215A-G1-1010 with Rack Bezel
- **TF-OPD-215ART-G1-1010**  
TF-OPD-215AR-G1-1010 with Resistive TouchScreen
- **TF-OPD-215ABT-G2-1010**  
TF-OPD-215AB-G1-1010 with ELO Resistive TouchScreen

## Optional Accessories

- **ARM-LA0115**  
Swivel Arm with VESA 75/100mm Standards
- **ARM-WK075-0**  
Wallmount Kit with VESA 75/100mm Standards
- **STAND-8150B0**  
Desktop Stand with VESA 100mm Standards
- **STAND-8150S0**  
Desktop Stand with VESA 100mm Standards (Silver)