# BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#:

Description:

k Type: Custom Pin Fin

60.00 x 60.00 x 2.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

ATS060060002-PF-16A

 Heat Sink Type:
 Custo

 Heat Sink Attachment:
 N/A

 Equivalent Part Number:
 N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	16.78 °C/W	10.9 °C/W	7.7 °C/W	6 °C/W	5.1 °C/W	4.4 °C/W	4 °C/W
	Ducted Flow	3.4	2.8	2.5	2.3	2.1	2	1.8

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
alla	60.00 mm	60.00 mm	2.00 mm	60 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal p application</li> <li>ATS resent performant</li> <li>ATS certifier</li> </ul>	<ul> <li>D is fin tip to fin tip performance data are</li> <li>n.</li> <li>ves the right to update</li> <li>vec.</li> </ul>	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf ducts without notice i-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@gats.com or www.gats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA