



ADAPTERS



FAX ON DEMAND This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (909) 469-2991. Enter the Pomona Access number (shown in italics) when prompted.


DOUBLE BANANA PLUG SPLICE



Provides rapid method for splicing cables.
 RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
 *STD. COLORS: -0 black, -2 red.

Pomona ACCESS	Model	PRICE
90550	1823-*	2.70


SINGLE BANANA PLUG SPLICE



Provides rapid method for splicing single banana plug patch cords.
 RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
 *STD. COLORS: -0 black, -2 red.
 Sold in pkgs. of 10.

Pomona ACCESS	Model	PRICE
90268	1829-*	1.40 ea.


DOUBLE BANANA JACK TO MINIATURE DOUBLE BANANA PLUG



Converts standard banana plugs to miniature.
 MATERIAL: Jack: Nickel Plated Brass; Spring: Nickel Plated Beryllium Copper; Insulation: ABS
 RATING: 2500 VDC, 5 Amps, +50°C (+122°F) Max.
 COLOR: Black

Pomona ACCESS	Model	PRICE
90563	2952	7.05

DOUBLE BANANA PLUG WITH BINDING POSTS



Features insulated binding posts on .750" centers for rapid mounting and interchangeability of components. Center cross hole (.166 dia.) provides side stackup connection.
 MATERIAL: Binding Post/Banana Plug Body: Brass; Spring: Beryllium Copper; Insulation: ABS
 RATING: 2500 VDC, 15 Amps, +50°C (+122°F) Max.
 COLOR: Black

Pomona ACCESS	Model	Plating	PRICE
90500	1286	Nickel	7.60
	5405	Gold	10.75


BANANA JACK TO MINIATURE BANANA PLUG



Use to mate standard (.166 dia.) banana plug to equipment having miniature banana jacks.
 MATERIAL: Same as 2952 above.
 RATING: 2500 VDC, 5 Amps, +50°C (+122°F) Max.
 *STD COLORS: -0 black, -2 red.
 Sold in pkgs. of 10.

Pomona ACCESS	Model	PRICE
90552	2138-*	1.90 ea.


BINDING POST TO BANANA PLUG



Features insulated binding post for rapid mounting and interchangeability of components. Accepts standard banana plug. Center cross hole (.166 dia.) provides side stackup connection.
 MATERIAL: Binding Post/Banana Plug Body: Nickel Plated Brass; Spring: Nickel Plated Beryllium Copper; Insulation: ABS
 RATING: 2500 VDC, 15 Amps, +50°C (+122°F) Max.
 *BINDING POST COLORS: -0 black, -2 red.

Pomona ACCESS	Model	PRICE
90560	2894-*	4.15


MINIATURE BANANA JACK TO BANANA PLUG



Converts miniature banana plugs to standard.
 MATERIAL: Same as 2952 above.
 RATING: 2500 VDC, 5 Amps, +50°C (+122°F) Max.
 *STD COLORS: -0 black, -2 red.
 Sold in pkgs. of 10.

Pomona ACCESS	Model	PRICE
90556	2477-*	1.70 ea.


PIN TIP JACK TO BANANA PLUG



Accepts .080 pin tip plug or probe tip. Fits standard (.166 dia.) banana jack.
 MATERIAL: Gold Plated Beryllium Copper
 RATING: 2500 VDC, 5 Amps, +50°C (+122°F) Max.
 *STD COLORS: -0 black, -2 red.
 Sold in pkgs. of 10.

Pomona ACCESS	Model	PRICE
90549	1809-*	1.95 ea.


BANANA JACK TO PIN TIP PLUG



Use to mate standard banana plug patch cords to equipment having pin jacks.
 MATERIAL: Jack/Plug: Nickel Plated Brass; Insulation: ABS
 RATING: 3000 VDC, 5 Amps, +50°C (+122°F) Max.
 *STD COLORS: -0 black, -2 red.
 Sold in pkgs. of 10.

Pomona ACCESS	Model	PRICE
90543	1432-*	1.05 ea.

INSULATED DOUBLE BANANA PLUG SHORTING BAR WITH BINDING POST



Fits standard banana jack. Shorting bar is completely insulated in clear ABS thermoplastic.
 MATERIAL: Binding Post/Banana Plug Body/Shorting Bar: Nickel Plated Brass; Spring: Nickel Plated Beryllium Copper; Insulation: Polycarbonate
 RATING: 2500 VDC, 15 Amps, +50°C (+122°F) Max.
 *BINDING POST COLORS: -0 blk, -2 red.

Pomona ACCESS	Model	PRICE
90623	5165-*	8.40

BANANA JACK TO .080" DIA. PIN TIP JACK



Adapts standard (.166 dia.) banana plug to .080 dia. pin tip plug.
 MATERIAL: Banana Jack: Nickel Plated Brass; Pin Jack: Gold Plated Beryllium Copper; Insulation: Polypropylene
 RATING: 3000 VDC, 5 Amps, +55°C (+131°F) Max.
 *STD. COLORS: -0 black, -2 red.

Pomona ACCESS	Model	PRICE
90585	3834-*	2.25