



#### General ordering data

|                  |   |
|------------------|---|
| Order No.        | 1938150150  |
| Part designation | SAIL-M8WM12W-4-1.5Q   |
| Version          | Sensor/Actuator line, Connecting line, LED: No,<br>1.50 m, PUR/ TPE |
| EAN              | 4032248611133   |
| Qty.             | 1 pc(s).  |

#### Technical data

|                           |                       |
|---------------------------|-----------------------|
| Ambient temperature, max. | 80 °C                 |
| Ambient temperature, min. | -50 °C                |
| Cable diameter, max.      | 4.9 mm                |
| Cable diameter, min       | 4.5 mm                |
| Connection cross-section  | 0,25                  |
| Contact material          | Ni/Au                 |
| Contact surface           | gold-plated           |
| Core cross-section        | 0.25 mm <sup>2</sup>  |
| Material                  | PUR/ TPE              |
| Protection class          | IP 67                 |
| Rated current             | 4 A                   |
| Rated voltage             | 60 V DC               |
| Sheathing colour          | black                 |
| jumpered                  | No                    |
| No. of poles              | 4                     |
| Version                   | pin, 90° - socket 90° |
| Cable length              | 1.5 m                 |

#### Classifications

|            |             |
|------------|-------------|
| ETIM 2.0   | EC000304    |
| ETIM 3.0   | EC001855    |
| eClass 4.1 | 27-06-00-00 |
| eClass 5.0 | 27-06-91-90 |
| eClass 5.1 | 27-06-91-90 |

### Similar products

| Order No.  | Part designation    | Version   |
|------------|---------------------|---|
| 1938151000 | SAIL-M8WM12W-4-10Q  | Sensor/Actuator line, Connecting line, LED: No, 10.00 m, PUR/ TPE |
| 1938150300 | SAIL-M8WM12W-4-3.0Q | Sensor/Actuator line, Connecting line, LED: No, 3.00 m, PUR/ TPE  |
| 1938150500 | SAIL-M8WM12W-4-5.0Q | Sensor/Actuator line, Connecting line, LED: No, 5.00 m, PUR/ TPE  |