# BGA Heat Sink (High Aspect Ratio Ext.) **Custom Pin Fin**



ATS Part#:

## Description:



Heat Sink Type: Heat Sink Attachment: N/A Equivalent Part Number: N/A

**Custom Pin Fin** 

ATS031031014-PF-10M

31.00 x 31.00 x 14.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.6 °C/W	4.2 °C/W	3.6 °C/W	3.2 °C/W	2.9 °C/W	2.7 °C/W	2.5 °C/W
	Ducted Flow	3.4	2.9	2.6	2.3	2.2	2	1.9

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
alka	31.00 mm	31.00 mm	14.00 mm	31 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimensior</li> <li>Dimensior</li> <li>Thermal p application</li> <li>ATS reserver</li> <li>performan</li> <li>ATS certification</li> </ul>	<ul> <li>D is fin tip to fin tip performance data are</li> <li>n.</li> <li>a.</li> <li>b. the right to update</li> <li>b. the right to update</li> </ul>	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf ducts without notice -6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA