


Kabelschuhe Terminals

Lötfreie Kabelschuhe ohne Isolation Solderless terminals, non insulated

Bauform Supply condition	Artikel-Nummer Part number	DIN 46234	Leiter- querschnitt Wire size mm ² AWG	Bolzen Stud M	Abmessungen mm Dimensions mm						Verp.-Einh. Stück Standard packing Piece	
					S	Ø d 1	d 3	L	a	r		
	RSQ 7125 A 5-16	●	>10-16	5	1,2	5,8	11,0	20,0	10,0	7,5	500	
	RSQ 7125 A 6-16	●	6	6	1,2	5,8	11,0	20,0	10,0	7,5	500	
	RSQ 7126 A 8-16	●			8	1,2	5,8	14,0	22,0	10,0	10,0	500
	RSQ 7127 A 10-16	●			10	1,2	5,8	18,0	24,0	10,0	12,0	500
	RSQ 7128 A 12-16	●			12	1,2	5,8	22,0	26,0	10,0	13,0	250
	RSQ 7226 A 12-16				12	1,5	5,8	32,0	36,0	10,0	18,0	250
	RSQ 7156 A 5-25	●	>16-25	4	5	1,5	7,5	12,0	25,0	11,0	7,5	250
	RSQ 7156 A 6-25	●			6	1,5	7,5	12,0	25,0	11,0	7,5	250
	RSQ 7130 A 6-25				6	1,5	7,5	16,0	25,0	11,0	10,0	250
	RSQ 7130 A 8-25	●			8	1,5	7,5	16,0	25,0	11,0	10,0	250
	RSQ 7131 A 10-25	●			10	1,5	7,5	18,0	26,0	11,0	12,0	250
	RSQ 7132 A 12-25	●			12	1,5	7,5	22,0	31,0	11,0	13,0	250
	RSQ 7214 A 12-25				12	1,8	7,5	30,0	36,5	11,0	17,0	250
	RSQ 7211 A 16-25	●			16	1,5	7,5	28,0	35,0	11,0	16,0	125
	RSQ 7229 A 6-35	●	>25-35	2	6	1,6	9,0	15,0	26,0	12,0	10,0	250
	RSQ 7134 A 8-35	●			8	1,6	9,0	16,0	26,0	12,0	10,0	250
	RSQ 7175 A 10-35	●			10	1,6	9,0	18,0	27,0	12,0	12,0	250
	RSQ 7135 A 12-35	●			12	1,6	9,0	22,0	31,0	12,0	13,0	125
	RSQ 7212 A 16-35	●			16	1,6	9,0	28,0	36,0	12,0	16,0	125
	RSQ 7187 A 16-35				16	1,8	9,0	30,0	37,5	12,0	18,0	125
	RSQ 7187 A 20-35				20	1,8	9,0	30,0	37,5	12,0	18,0	125
	RSQ 7136 A 6-50	●	>35-50	1/0	6	1,8	11,0	18,0	34,0	16,0	12,0	125
	RSQ 7136 A 8-50	●			8	1,8	11,0	18,0	34,0	16,0	12,0	125
	RSQ 7136 A 10-50	●			10	1,8	11,0	18,0	34,0	16,0	12,0	125
	RSQ 7137 A 12-50	●			12	1,8	11,0	22,0	36,0	16,0	13,0	125
	RSQ 7139 A 16-50	●			16	1,8	11,0	28,0	40,0	16,0	16,0	125
	RSQ 7193 A 16-50				16	2,0	11,0	32,0	41,5	16,0	18,0	250
	RSQ 7193 A 20-50				20	2,0	11,0	32,0	41,5	16,0	18,0	100
RSQ 7140 A 6-70	●	>50-70	2/0	6	2,0	13,0	22,0	38,0	18,0	13,0	100	
RSQ 7140 A 8-70	●			8	2,0	13,0	22,0	38,0	18,0	13,0	100	
RSQ 7140 A 10-70	●			10	2,0	13,0	22,0	38,0	18,0	13,0	100	
RSQ 7140 A 12-70	●			12	2,0	13,0	22,0	38,0	18,0	13,0	100	
RSQ 7142 A 16-70	●			16	2,0	13,0	28,0	42,0	18,0	16,0	100	
RSQ 7188 A 16-70				16	2,0	13,0	32,0	45,0	18,0	18,0	100	
RSQ 7188 A 20-70				20	2,0	13,0	32,0	45,0	18,0	18,0	100	
RSQ 7144 A 8-95	●	>70-95	3/0	8	2,5	15,0	24,0	42,0	20,0	13,0	100	
RSQ 7144 A 10-95	●			10	2,5	15,0	24,0	42,0	20,0	13,0	100	
RSQ 7177 A 10-95				10	2,3	15,0	27,0	41,0	20,0	14,0	100	
RSQ 7144 A 12-95	●			12	2,5	15,0	24,0	42,0	20,0	13,0	100	
RSQ 7177 A 12-95				12	2,3	15,0	27,0	41,0	20,0	14,0	100	
RSQ 7145 A 16-95	●			16	2,5	15,0	28,0	44,0	20,0	16,0	100	
RSQ 7177 A 16-95				16	2,3	15,0	27,0	41,0	20,0	14,0	100	
RSQ 7194 A 16-95				16	2,3	15,0	32,0	52,0	20,0	18,0	100	
RSQ 7194 A 20-95				20	2,3	15,0	32,0	52,0	20,0	18,0	100	

Material: SE-Cu, galv. verzinkt
Material: electrolytic copper, electro-tinned