

COPPER CABLING SOLUTIONS

UL **PAN-PLUG™ High Performance Modular Plugs**

- Unique tangle free plug latch prevents snags and provides easy release, saving time on frequent moves, adds and changes
- Exceeds FCC Part 68 and IEC 603-7 specifications
- Used in UTPCH series patch cords providing Category 5 Powersum performance

- Simplifies termination due to a unique process which requires no loading bar. Guide ramp facilitates easy conductor insertion and termination. Simplified termination design means fewer pieces required and reduces handling of small parts.
- Contacts plated with 50 microinches of gold



MP588-L



WPT-8

- Arranges all eight conductors in the proper sequence
- Provides an easy way to cut conductors to the required length



CT5-8

- Required for *PAN-PLUG* Modular Plug termination

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	----------------	----------------

PAN-PLUG Modular Plugs

MP588-L	8 Position, 8 Wire Modular Plug featuring tangle free latch. Terminates 24 gauge stranded or solid conductor with max. conductor insulation diameter of 1.02mm. CT5-8 Crimp Tool required for termination.	50	250
----------------	--	----	-----

Wire Prep Tool

WPT-8	Wire Prep Tool	1	10
--------------	----------------	---	----

PAN-PLUG Installation Tools

CT5-8	Crimp tool and die for <i>PAN-PLUG</i> Modular Plug	1	—
CD5-8	Crimp die only	1	—

UL **TX-6™ Patch Cords**

- Features Next Generation stranded cable and enhanced performance modular plugs with *GIGA-TX™* Technology for superior performance
- Offered in a variety of sizes and colours to meet individual length and colour coding requirements



Part Number	Description	Cable Colour‡	Length (m)	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	---------------	------------	----------------	----------------

TX-6 Patch Cords

UTPCTG1M	Patch Cords for use with <i>TX-6</i> Modules (CJ688T & CJ688T3).	Off White	1	1	10
UTPCTG2M		Off White	2		
UTPCTG3M		Off White	3		
UTPCTG4M		Off White	4		
UTPCTG5M		Off White	5		
UTPCTG10M		Off White	10		

‡For other cable colours add suffix BL (Black), BU (Blue), GR (Green), RD (Red) and YL (Yellow) after part number.

TX-6 Shielded Patch Cords



Part Number	Description	Boot Colour	Length (m)	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	-------------	-------------	------------	----------------	----------------

TX-6 Shielded Patch Cords

STPCTG1MBBL	Shielded Patch Cords for use with <i>TX-6</i> Shielded Modules (CJS688T & CJS688T3).	Black	1	1	10
STPCTG2MBBL		Black	2	1	10
STPCTG3MBBL		Black	3	1	10
STPCTG5MBBL		Black	5	1	10

Note: For other boot colours replace BL (Black) with suffix BU (Blue), GR (Green), RD (Red) and YL (Yellow).

Patch Panels can be found on pages 54-57