

TRANSZORB® Transient Voltage Suppressors

ICTE5 thru ICTE18C, 1N6373 thru 1N6386

| PRIMARY CHARACTERISTICS | |
|-------------------------|---------------|
| V _{WM} | 5.0 V to 18 V |
| P _{PPM} | 1500 W |
| P _D | 6.5 W |
| I _{FSM} | 200 A |
| T _J max. | 175 °C |

DEVICES FOR BI-DIRECTION APPLICATIONS

For bi-directional types, use C suffix (e.g. ICTE18C).
Electrical characteristics apply in both directions.

FEATURES

- Glass passivated chip junction
- Available in uni-directional and bi-directional
- 1500 W peak pulse power capability with a 10/1000 μ s waveform, repetitive rate (duty cycle): 0.01 %
- Excellent clamping capability
- Very fast response time
- Low incremental surge resistance
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- AEC-Q101 qualified

TYPICAL APPLICATIONS

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting on ICs, MOSFET, signal lines of sensor units for consumer, computer, industrial and telecommunication.

MECHANICAL DATA

Case: Molded epoxy body over passivated junction
Molding compound meets UL 94 V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102
E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

Polarity: For uni-directional types the color band denotes cathode end, no marking on bi-directional types

| MAXIMUM RATINGS (T _A = 25 °C unless otherwise noted) | | | |
|---|-----------------------------------|----------------|------|
| PARAMETER | SYMBOL | LIMIT | UNIT |
| Peak pulse power dissipation with a 10/1000 μ s waveform ⁽¹⁾ (fig. 1) | P _{PPM} | 1500 | W |
| Peak pulse current with a 10/1000 μ s waveform ⁽¹⁾ (fig. 3) | I _{PPM} | See next table | A |
| Power dissipation on infinite heatsink at T _L = 75 °C (fig. 8) | P _D | 6.5 | W |
| Peak forward surge current 8.3 ms single half sine-wave uni-directional only ⁽²⁾ | I _{FSM} | 200 | A |
| Maximum instantaneous forward voltage at 100 A for uni-directional only | V _F | 3.5 | V |
| Operating junction and storage temperature range | T _J , T _{STG} | - 55 to + 175 | °C |

Notes

⁽¹⁾ Non-repetitive current pulse, per fig. 3 and derated above T_A = 25 °C per fig. 2

⁽²⁾ 8.3 ms single half sine-wave, duty cycle = 4 pulses per minute maximum



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

ELECTRICAL CHARACTERISTICS (JEDEC REGISTERED DATA) ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)

| JEDEC TYPE NUMBER | GENERAL SEMICONDUCTOR PART NUMBER | STAND-OFF VOLTAGE V_{WM} (V) | MINIMUM BREAKDOWN VOLTAGE AT 1.0 mA V_{BR} (V) | MAXIMUM REVERSE LEAKAGE AT V_{WM} I_D (μA) | MAXIMUM CLAMPING VOLTAGE AT $I_{PP} = 1.0\text{ A}$ V_C (V) | MAXIMUM CLAMPING VOLTAGE AT $I_{PP} = 10\text{ A}$ V_C (V) | MAXIMUM PEAK PULSE CURRENT I_{PP} (A) |
|------------------------------|-----------------------------------|--------------------------------|--|---|---|--|---|
| UNI-DIRECTIONAL TYPES | | | | | | | |
| 1N6373 ⁽²⁾ | ICTE5 ⁽²⁾ | 5.0 | 6.0 | 300 | 7.1 | 7.5 | 160 |
| 1N6374 | ICTE8 | 8.0 | 9.4 | 25.0 | 11.3 | 11.5 | 100 |
| 1N6375 | ICTE10 | 10.0 | 11.7 | 2.0 | 13.7 | 14.1 | 90 |
| 1N6376 | ICTE12 | 12.0 | 14.1 | 2.0 | 16.1 | 16.5 | 70 |
| 1N6377 | ICTE15 | 15.0 | 17.6 | 2.0 | 20.1 | 20.6 | 60 |
| 1N6378 | ICTE18 | 18.0 | 21.2 | 2.0 | 24.2 | 25.2 | 50 |
| BI-DIRECTIONAL TYPES | | | | | | | |
| 1N6382 | ICTE8C | 8.0 | 9.4 | 50.0 | 11.4 | 11.6 | 100 |
| 1N6383 | ICTE10C | 10.0 | 11.7 | 2.0 | 14.1 | 14.5 | 90 |
| 1N6384 | ICTE12C | 12.0 | 14.1 | 2.0 | 16.7 | 17.1 | 70 |
| 1N6385 | ICTE15C | 15.0 | 17.6 | 2.0 | 20.8 | 21.4 | 60 |
| 1N6386 | ICTE18C | 18.0 | 21.2 | 2.0 | 24.8 | 25.5 | 50 |

Notes

- (1) "C" suffix indicates bi-directional
- (2) ICTE5 and 1N6373 are not available as bi-directional
- (3) Clamping factor: 1.33 at full rated power; 1.20 at 50 % rated power; clamping factor: the ratio of the actual V_C (clamping voltage) to the V_{BR} (breakdown voltage) as measured on a specific device

ORDERING INFORMATION (Example)

| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
|----------------------------|-----------------|------------------------|---------------|----------------------------------|
| ICTE5-E3/54 | 0.968 | 54 | 1400 | 13" diameter paper tape and reel |
| ICTE5HE3/54 ⁽¹⁾ | 0.968 | 54 | 1400 | 13" diameter paper tape and reel |

Note

- (1) Automotive grade

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

