


- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 5A @120VAC OR 28VDC
2A @250VAC
 5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
 6. INSULATION RESISTANCE: 1,000M ohm min.
 7. DIELECTRIC STRENGTH: 1000V RMS @sea level
 8. OPERATING TEMP.: -30°C to 85°C
 9. 2002/95/EC (ROHS) COMPLIANT



CIRCUIT: SPDT
CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
<DN>	OFF	<DN>	
2-3	OPEN	2-1	

() = MOMENTARY

E-SWITCH®

100SP4T1B9M1QE

B	16806	NOTES UPDATED, REVISED	12/28/06	TN
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
100SP4T1B9M1QE		2:1	12/28/06	TN	T114017	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED