



Micro Commercial Components



Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

# MCU04N60

## N-Channel Enhancement Mode Field Effect Transistor


### Features

- High Current Rating
- Lower Capacitance
- Halogen free available upon request by adding suffix "-HF"
- Lower  $R_{DS(ON)}$
- Lower Total Gate Charge
- Tighter VSD Specifications
- Avalanche Energy Specified
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


### Maximum Ratings @ 25°C Unless Otherwise Specified

Symbol	Parameter	Rating	Unit
$V_{DS}$	Drain-source Voltage	600	V
$I_D$	Drain Current-Continuous	4.0	A
$I_S$	Continuous Drain-Source Diode Forward Current	4.0	A
$V_{GSS}$	Gate-source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulsed Avalanche Energy(note1)	260	mJ
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	100	$^{\circ}C/W$
$T_J$	Operating Junction Temperature	-55 to +150	$^{\circ}C$
$T_{STG}$	Storage Temperature	-55 to +150	$^{\circ}C$
$T_L$	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	260	$^{\circ}C$

### Internal Block Diagram



### DPAK



- 1.GATE
- 2.DRAIN
- 3.SOURCE

DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.087	0.094	2.20	2.40	
B	0.000	0.005	0.00	0.13	
C	0.026	0.034	0.66	0.86	
D	0.018	0.023	0.46	0.58	
E	0.256	0.264	6.50	6.70	
F	0.201	0.215	5.10	5.46	
G	0.190		4.83		
H	0.236	0.244	6.00	6.20	
I	0.086	0.094	2.18	2.39	
J	0.386	0.409	9.80	10.40	
K	0.114		2.90		
L	0.055	0.067	1.40	1.70	
M	0.063		1.60		
O	0.043	0.051	1.10	1.30	
Q	0.000	0.012	0.00	0.30	
V	0.211		5.35		

**Electrical characteristics (T<sub>a</sub>=25°C unless otherwise noted)**

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Off characteristics</b>						
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> =250μA	600			V
Drain-source diode forward voltage(note2)	V <sub>SD</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> =4.0A			1.5	
Zero gate voltage drain current	I <sub>DSS</sub>	V <sub>DS</sub> =600V, V <sub>GS</sub> =0V			25	μA
Gate-body leakage current, forward(note2)	I <sub>GSSF</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =30V			100	nA
Gate-body leakage current, reverse(note2)	I <sub>GSSR</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =-30V			-100	
<b>On characteristics (note2)</b>						
Gate-threshold voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	2.0		4.0	V
Static drain-source on-resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =2.0A		2.0	3.0	Ω
Forward transconductance	g <sub>fs</sub>	V <sub>DS</sub> =50V, I <sub>D</sub> =2A	2.5			S
<b>Dynamic characteristics (note 3)</b>						
Input capacitance	C <sub>iss</sub>	V <sub>DS</sub> =25V, V <sub>GS</sub> =0V, f =1MHz		540	760	pF
Output capacitance	C <sub>oss</sub>			125	180	
Reverse transfer capacitance	C <sub>rss</sub>			8.0	20	
<b>Switching characteristics</b>						
Total gate charge	Q <sub>g</sub>	V <sub>DS</sub> =480V, V <sub>GS</sub> =10V, I <sub>D</sub> =4.0A		5.0	10	nC
Gate-source charge	Q <sub>gs</sub>			2.7		
Gate-drain charge	Q <sub>gd</sub>			2.0		
Turn-on delay time (note3)	t <sub>d(on)</sub>	V <sub>DD</sub> =300V, V <sub>GS</sub> =10V, R <sub>G</sub> =9.1Ω, I <sub>D</sub> =4.0A		12	20	ns
Turn-on rise time (note3)	t <sub>r</sub>			7.0	10	
Turn-off delay time (note3)	t <sub>d(off)</sub>			19	40	
Turn-off fall time (note3)	t <sub>f</sub>			10	20	

**Notes :**

- L=30mH, I<sub>L</sub>=4 A, V<sub>DD</sub>=100V, V<sub>GS</sub>=10V, R<sub>G</sub>=25Ω, Starting T<sub>J</sub>=25°C.
- Pulse Test : Pulse width≤300μs, duty cycle ≤2%.
- These parameters have no way to verify.



TM

Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

[www.mccsemi.com](http://www.mccsemi.com)